



## SPECS

FRAME	
<b>SIZES</b>	S, M, L, XL
<b>COLOURS</b>	Asphalt Green, Solar Flare
<b>FRAME</b>	ALUXX SL-grade aluminum, 12x148mm thru-axle
<b>FORK</b>	Giant STL 34, RCL, 140mm, 44mm offset, Boost 15x110
<b>SHOCK</b>	N/A
COMPONENTS	
<b>HANDLEBAR</b>	Giant Contact SL TR35, 780x35mm
<b>GRIPS</b>	Giant Sole-O
<b>STEM</b>	Giant Contact SL 35 S:40mm, M:40mm, L:50mm, XL:50mm
<b>SEATPOST</b>	Giant Contact Switch AT dropper, remote S: 110-140mm travel / 30.9 x 395mm
<b>SADDLE</b>	Giant Romero
DRIVETRAIN	
<b>SHIFTERS</b>	Shimano CUES SL-6000, 1x10
<b>FRONT DERAILLEUR</b>	N/A
<b>REAR DERAILLEUR</b>	Shimano CUES RD-U6000
<b>BRAKES</b>	Shimano BR-MT420, hydraulic, Shimano RT-26 rotors [F]180mm, [R]180mm
<b>BRAKE LEVERS</b>	Shimano MT-401
<b>CASSETTE</b>	Shimano CUES, CS-LG300, 11x48
<b>CHAIN</b>	KMC X-11
<b>CRANKSET</b>	Shimano CUES FC-U6000, 30t S:170mm, M:170mm, L:170mm, XL:170mm
<b>BOTTOM BRACKET</b>	Shimano, threaded

WHEELS	
<b>RIMS</b>	Giant AM 27.5, tubeless ready sleeve-joint rim, 30mm inner width
<b>HUBS</b>	alloy, sealed
<b>SPOKES</b>	stainless
<b>TIRES</b>	(F) DHF 27.5x2.5" (R) Maxxis Dissector 27.5x2.4"
<b>EXTRAS</b>	tubeless prepared, 2.6" max tire size, 32t max chainring size

**Suggested Retail Price (CDN): \$1,899.00**

## FRAME GEOMETRY

FRAME	S	M	L
Seat Tube Length (mm)	380	430	465
Seat Post Insertion Depth (mm)	300	200	235
Seat Tube Angle	75.0°	75.0°	75.0°
Top Tube Length (mm)	592	612	639
Head Tube Length (mm)	95	95	105
Head Tube Angle	66.0°	66.0°	66.0°
Fork Rake (mm)	44	44	44
Trail (mm)	113	113	113
Wheelbase (mm)	1157	1177	1206
Chain Stay Length (mm)	438	438	438
Bottom Bracket Drop (mm)	60	60	60
Stack (mm)	622	622	631
Reach (mm)	425	445	470
Stand Over Height (mm)	708	727	746
Handlebar Width (mm)	780	780	780
Stem Length (mm)	40	40	50
Crank Length (mm)	165	170	170
Wheel Size	27.5"	27.5"	27.5"

*All prices and specifications are subject to change without notice.*