



## СПЕЦИФИКАЦИИ

РАМКА	
РАЗМЕР	S/M, M/L, L/XL
ЦВЯТ	Shoreline/Carbon
РАМКА	Advanced-grade composite front and rear triangles, 200mm Maestro suspension, flip chip - headset, flip chip - dropout DH, flip chip - Maestro 3, 12x157mm thru-axle, 27.5 or 29-inch rear wheel compatible
ВИЛКА	Fox 40 Factory, GRIP2 damper, 203mm, 20x110, custom tuned for Giant
ЗАДЕН АМОРТИСЬОР	Fox DHX2 Factory, SLS coil, 225/75, custom tuned for Giant S/M #425, M/L #450, L/XL #475
КОМПОНЕНТИ	
КОРМИЛО	Giant Contact SL TR35, composite, 800x35mm, 20mm rise
ГРИПОВЕ	Giant Tactal Pro Single
ЛАПА	TruVativ Descendant Direct Mount, 35 S/M:50mm, M/L:50mm, L/XL:50mm
КОЛЧЕ ЗА СЕДАЛКА	Giant Contact, 30.9mm, 0 offset, 400mm
СЕДАЛКА	Giant Romero
DRIVETRAIN	
КОМАНДИ	SRAM GX Eagle DH, 1x7
ПРЕДЕН ДЕРАЙЛЪОР	N/A
ЗАДЕН ДЕРАЙЛЪОР	SRAM GX Eagle DH
СПИРАЧКИ	Shimano Saint M-820, hydraulic, Shimano RT-66 rotors, [F]220mm, [R]203mm
РЪКОХВАТКИ ЗА СПИРАЧКИ	Shimano Saint BL-M820
КАСЕТА	SRAM GX DH, 11-25
ВЕРИГА	SRAM PC 1110
КУРБЕЛ	TruVativ Descendant DH, 34t, 56.5mm chainline, S/M:165mm, M/L:170mm, L/XL:170mm
СРЕДНА КАСЕТА	SRAM DUB, threaded, 83mm

КАПЛИ	
ШИНИ	Giant AM30, alloy, 28-hole, 30mm inner width
ГЛАВИНИ	[F] alloy, sealed cartridge, 6-bolt, 20x110mm [R] alloy, 72t pawl driver, sealed cartridge, 6-bolt, 12x157mm
СПИЦИ	Sapim Laser, straight pull, DBL
ГУМИ	[F] Maxxis Assegai 29x2.5 WT, 3C MaxxGrip, DH, TR [R] Maxxis Minion DHR II 27.5x2.4 WT, 3C, MaxxGrip, DH, TR tubeless
ЕКСТРИ	tubeless prepared, 2.5" max tire size, 36t max chainring size, MRP SXg chain guide, full downtube protector. *Not compatible with 2023 or earlier RockShox BoXXer Ultimate or BoXXer Select

## ГЕОМЕТРИЯ

РАМКА	S/M			M/L			L/XL		
	LOW	MID	HIGH	LOW	MID	HIGH	LOW	MID	HIGH
Seat Tube Length (mm)	430			450			450		
Seat Post Insertion Depth (mm)	155			165			165		
Seat Tube Angle	78,4°   78,7°   79,1°			78,4°   78,8°   79,1°			78,5°   78,8°   79,1°		
Top Tube Length (mm)	571,2   570,5   569,8			591,3   590,5   589,8			611,3   610,6   609,8		
Head Tube Length (mm)	110			110			110		
Head Tube Angle	61,6°   61,9°   62,3°			61,6°   62,0°   62,3°			61,7°   62,0°   62,3°		
Fork Rake (mm)	52			52			52		
Trail (mm)	146,4   143,6   140,8			146,2   143,5   140,8			146   143,3   140,8		
Wheelbase (mm)	1273   1271,9   1270,6			1293   1291,8   1290,6			1313   1311,9   1310,6		
Chain Stay Length (mm)	447,9   446,5   445			447,9   446,5   445			447,9   446,5   445		
Bottom Bracket Drop (mm)	13,1   8,1   3			13,3   8,3   3,1			13,5   8,4   3,2		
Stack (mm)	634,6   631,9   629,1			634,9   632,2   629,2			635,3   632,4   629,3		
Обсер (mm)	440,9   444,7   448,6			461,2   464,9   468,6			481,5   485,1   488,6		
Stand Over Height (mm)	733,7   738,2   742,9			735,2   740   744,8			742,9   747,6   752,3		
Ширина на Кормило (mm)	800			800			800		
Дължина на Лапа (mm)	50			50			50		
Дължина на Курбел (mm)	165			165			165		
Размер на Каплите	[R] 27.5" / [F] 29"			[R] 27.5" / [F] 29"			[R] 27.5" / [F] 29"		

All specifications listed are subject to change without notice.