GLORY ADVANCED



SPECIFIKATIONER

RAMME	
STØRRELSER	S/M, M/L, L/XL
FARVER	Moon Dust
RAMME	Advanced-grade composite front and rear triangles, 200mm Maestro suspension, flip chip - headset, flip chip - dropout DH, flip chip - Maestro 3, 12x157mm thru-axle, 27.5 or 29-inch rear wheel compatible
FORGAFFEL	Fox 40 Factory, GRIP X2 damper, 203mm, 20x110
BAGDÆMPER	Fox DHX2 Factory, SLS coil, 225/75 S/M:425#, M/L:450#, L/XL:475#
KOMPONENTER	
STYR	Giant Contact SL TR35, 800x35mm, 20mm rise
GREB / STYRBÅND	Giant Tactal Pro Single
FREMPIND	TruVativ Descendant Direct Mount 35 S/M:50mm, M/L:50mm, L/XL:50mm
SADELPIND	Giant Contact, 30.9mm, 0 offset, 400mm
SADEL	Giant Romero
PEDALER	platform [GC,GT]
GEARGRUPPE	
SKIFTEGREB	TRP EVO 7 DH, 1x7
FORSKIFTER	N/A
BAGSKIFTER	TRP EVO 7 DH
BREMSER	TRP EVO Pro, hydraulic, TRP rotors [F]220mm, [R]203mm
BREMSEGREB	TRP EVO Pro
KASSETTE	TRP EVO 7 DH, 11-24
KÆDE	KMC X-11
KRANKSÆT	TRP EVO 7 DH, 34t, 56.5mm chainline S/M:165mm, M/L:165mm, L/XL:165mm
KRANKBOKS	TRP, threaded, 83mm

HJUL	
FÆLGE	Giant TRA 2 rims, 6061 alloy, hookless, 30mm inner width, 40mm outer width, 21mm height, Wide Guard Technology
NAV	[F] Giant MTB alloy, 6-bolt [R] Giant MTB alloy, 30t 3-pawl driver, 6-bolt
EGER	Stainless steel
DÆK	[F] Maxxis Assegai 29x2.5 WT, 3C MaxxGrip, DH, TR [R] Maxxis Minion DHR II 27.5x2.4 WT, 3C, MaxxGrip, DH, TR tubeless
EKSTRA	tubeless prepared, 2.5" max tire size, 36t max chainring size, MRP SXg chain guide, full down tube protector

Pris: 63.529,00 kr.

GEOMETRI

RAMME	L/XL	M/L
	LOW | MID | HIGH	LOW | MID | HIGH
Sadelrørslængde (mm)	450	450
Sadelpindindsætningsdybde (mm)	165	165
Sadelrørsvinkel	78,5° | 78,8° | 79,1°	78,4° | 78,8° | 79,1°
Overrørslængde (mm)	611 | 611 | 610	591 | 591 | 590
Kronrørslængde (mm)	110	110
Kronrøsvinkel	61,7° | 62,0° | 62,3°	61,6° | 62,0° | 62,3°
Forgaffel fremspring (rake) (mm)	52	52
Sti (mm)	146 | 143,3 | 140,8	146,2 | 143,5 | 140,8
Akselafstand (mm)	1313 | 1312 | 1311	1293 | 1292 | 1291
Kædestagslængde (mm)	448 | 447 | 445	448 | 447 | 445
Krankboks drop (mm)	14 | 8 | 3	13 | 8 | 3
Stack (mm)	635 | 632 | 629	635 | 632 | 629
Reach (mm)	482 | 485 | 489	461 | 465 | 469
Skridthøjde (mm)	743 | 748 | 752	735 | 740 | 745
Styrbredde (mm)	800	800
Frempindslængde (mm)	50	50
Pedalarmslængde (mm)	165	165

Alle de anførte specifikationer kan ændres uden varsel.