



SPEZIFIKATIONEN

RAHMEN	
GRÖSSEN	S/M, M/L, L/XL
FARBE	Black Lava/Mercury/Chrome
RAHMEN	Advanced-grade composite front and rear triangles, 200mm Maestro suspension, flip chip - headset, flip chip - dropout DH, flip chip - Maestro 3, 12x157mm thru-axle, 27.5 or 29-inch rear wheel compatible
GABEL	Fox 40 Factory, GRIP X2 damper, 203mm, 20x110
DÄMPFER	Fox DHX2 Factory, SLS coil, 225/75, custom tuned for Giant S/M:425#, M/L:450#, L/XL:475#
KOMPONENTEN	
LENKER	Giant Contact SL TR35, 800x35mm, 20mm rise
GRIFFE	Giant Tactal Pro Single
VORBAU	TruVativ Descendant Direct Mount 35 S/M:50mm, M/L:50mm, L/XL:50mm
SATTELSTÜTZE	Giant Contact, 30.9mm, 0 offset, 400mm
SATTEL	Giant Romero
ANTRIEB	
SCHALTHEBEL	SRAM GX Eagle DH, 1x7
UMWERFER	N/A
SCHALTWERK	SRAM GX Eagle DH
BREMSEN	Shimano Saint M-820, hydraulic, Shimano RT-66 rotors [F]220mm, [R]203mm
BREMSHEBEL	Shimano Saint BL-M820
KASSETTE	SRAM GX DH, 11-25
KETTE	SRAM PC 1110
KURBEL	TruVativ Descendent DH, 34t, 56.5mm chainline S/M:165mm, M/L:170mm, L/XL:170mm
TRETLAGER	SRAM DUB, threaded, 83mm

LAUFRÄDER	
FELGEN	Giant TRA 2 rims, 6061 alloy, hookless, 30mm inner width, 40mm outer width, 21mm height, Wide Guard Technology
NABE	[F] Giant MTB alloy, 6-bolt, [R] Giant MTB alloy, 30t 3-pawl driver, 6-bolt
SPEICHEN	Stainless steel
REIFEN	[F] Maxxis Assegai 29x2.5 WT, 3C MaxxGrip, DH, TR [R] Maxxis Minion DHR II 27.5x2.4 WT, 3C, MaxxGrip, DH, TR tubeless
EXTRAS	tubeless prepared, 2.5" max tire size, 36t max chainring size, MRP SXg chain guide, full down tube protector

GEOMETRIEDATEN

RAHMEN	S/M	M/L	L/XL
	LOW MID HIGH	LOW MID HIGH	LOW MID HIGH
Sitzrohrlänge (mm)	430	450	450
Seat Post Insertion Depth (mm)	155	165	165
Sitzrohrwinkel	78.4° 78.7° 79.1°	78.4° 78.8° 79.1°	78.5° 78.8° 79.1°
Oberrohrlänge (mm)	571.2 570.5 569.8	591.3 590.5 589.8	611.3 610.6 609.8
Steuerrohr-Länge (mm)	110	110	110
Steuerrohr-Winkel	61.6° 61.9° 62.3°	61.6° 62.0° 62.3°	61.7° 62.0° 62.3°
Gabelneigung (mm)	52	52	52
Trail (mm)	146.4 143.6 140.8	146.2 143.5 140.8	146 143.3 140.8
Radstand (mm)	1273 1271.9 1270.6	1293 1291.8 1290.6	1313 1311.9 1310.6
Kettenstreben-Länge (mm)	447.9 446.5 445	447.9 446.5 445	447.9 446.5 445
Tretlager-Höhe (mm)	13.1 8.1 3	13.3 8.3 3.1	13.5 8.4 3.2
Stack (mm)	634.6 631.9 629.1	634.9 632.2 629.2	635.3 632.4 629.3
Reach (mm)	440.9 444.7 448.6	461.2 464.9 468.6	481.5 485.1 488.6
Überstandshöhe (mm)	733.7 738.2 742.9	735.2 740 744.8	742.9 747.6 752.3
Lenkerbreite (mm)	800	800	800
Vorbaulänge (mm)	50	50	50
Kurbellänge (mm)	165	165	165
Radgrösse	[R] 27.5" / [F] 29"	[R] 27.5" / [F] 29"	[R] 27.5" / [F] 29"

Spezifikations-, Preis- und Farbänderungen vorbehalten.