



SPECS

ΣΚΕΛΕΤΟΣ	
ΜΕΓΕΘΗ	S/M, M/L, L/XL
ΧΡΩΜΑΤΑ	Shoreline/Carbon
ΣΚΕΛΕΤΟΣ	Advanced-grade composite front and rear triangles, 200mm Maestro suspension, flip chip - headset, flip chip - dropout DH, flip chip - Maestro 3, 12x157mm thru-axle, 27.5 or 29-inch rear wheel compatible
ΠΙΡΟΥΝΙ	Fox 40 Factory, GRIP2 damper, 203mm, 20x110, custom tuned for Giant
ΑΝΑΡΤΗΣΗ	Fox DHX2 Factory, SLS coil, 225/75, custom tuned for Giant S/M #425, M/L #450, L/XL #475
ΕΞΑΡΤΗΜΑΤΑ	
ΤΙΜΟΝΙ	Giant Contact SL TR35, composite, 800x35mm, 20mm rise
GRIPS	Giant Tactal Pro Single
ΛΑΙΜΟΣ ΤΙΜΟΝΙΟΥ	TruVativ Descendant Direct Mount, 35 S/M:50mm, M/L:50mm, L/XL:50mm
ΛΑΙΜΟΣ ΣΕΛΛΑΣ	Giant Contact, 30.9mm, 0 offset, 400mm
ΣΕΛΛΑ	Giant Romero
ΜΕΤΑΔΟΣΗ	
ΛΕΒΙΕ ΤΑΧΥΤΗΤΩΝ	SRAM GX Eagle DH, 1x7
ΝΤΕΡΑΓΓΙΕΡ ΕΜΠΡΟΣΘΙΟ	N/A
ΝΤΕΡΑΓΓΙΕΡ ΟΠΙΣΘΙΟ.	SRAM GX Eagle DH
ΦΡΕΝΑ	Shimano Saint M-820, hydraulic, Shimano RT-66 rotors, [F]220mm, [R]203mm
ΜΑΝΕΤΤΕΣ ΦΡΕΝΩΝ	Shimano Saint BL-M820
CASETTE Ή ΕΛΕΥΘΕΡΟ	SRAM GX DH, 11-25
ΑΛΥΣΙΔΑ	SRAM PC 1110
ΔΙΣΚΟΒΡΑΧΙΩΝΑΣ	TruVativ Descendent DH, 34t, 56.5mm chainline, S/M:165mm, M/L:170mm, L/XL:170mm
BOTTOM BRACKET	SRAM DUB, threaded, 83mm

WHEELS	
ΣΤΕΦΑΝΙΑ	Giant AM30, alloy, 28-hole, 30mm inner width
ΚΕΝΤΡΑ	[F] alloy, sealed cartridge, 6-bolt, 20x110mm [R] alloy, 72t pawl driver, sealed cartridge, 6-bolt, 12x157mm
ΑΚΤΙΝΕΣ	Sapim Laser, straight pull, DBL
ΕΛΑΣΤΙΚΑ	[F] Maxxis Assegai 29x2.5 WT, 3C MaxxGrip, DH, TR [R] Maxxis Minion DHR II 27.5x2.4 WT, 3C, MaxxGrip, DH, TR tubeless
EXTRAS	tubeless prepared, 2.5" max tire size, 36t max chainring size, MRP SXg chain guide, full downtube protector. *Not compatible with 2023 or earlier RockShox BoXXer Ultimate or BoXXer Select

ΓΕΩΜΕΤΡΙΑ

ΣΚΕΛΕΤΟΣ	S/M	M/L	L/XL
	LOW MID HIGH	LOW MID HIGH	LOW MID HIGH
Seat Tube Length (mm)	430	450	450
Seat Post Insertion Depth (mm)	155	165	165
Seat Tube Angle	78,4° 78,7° 79,1°	78,4° 78,8° 79,1°	78,5° 78,8° 79,1°
Top Tube Length (mm)	571,2 570,5 569,8	591,3 590,5 589,8	611,3 610,6 609,8
Head Tube Length (mm)	110	110	110
Head Tube Angle	61,6° 61,9° 62,3°	61,6° 62,0° 62,3°	61,7° 62,0° 62,3°
Fork Rake (mm)	52	52	52
Trail (mm)	146,4 143,6 140,8	146,2 143,5 140,8	146 143,3 140,8
Wheelbase (mm)	1273 1271,9 1270,6	1293 1291,8 1290,6	1313 1311,9 1310,6
Chain Stay Length (mm)	447,9 446,5 445	447,9 446,5 445	447,9 446,5 445
Bottom Bracket Drop (mm)	13,1 8,1 3	13,3 8,3 3,1	13,5 8,4 3,2
Stack (mm)	634,6 631,9 629,1	634,9 632,2 629,2	635,3 632,4 629,3
Reach (mm)	440,9 444,7 448,6	461,2 464,9 468,6	481,5 485,1 488,6
Stand Over Height (mm)	733,7 738,2 742,9	735,2 740 744,8	742,9 747,6 752,3
Handlebar Width (mm)	800	800	800
Stem Length (mm)	50	50	50
Crank Length (mm)	165	165	165
Wheel Size	[R] 27.5" / [F] 29"	[R] 27.5" / [F] 29"	[R] 27.5" / [F] 29"

Όλες οι προδιαγραφές είναι δυνατό να αλλάξουν χωρίς πρότερη ειδοποίηση