



SPECS

FRAME	
SIZES	S/M, M/L, L/XL
COLOURS	Shoreline/Carbon
FRAME	Advanced-grade composite front and rear triangles, 200mm Maestro suspension, flip chip - headset, flip chip - dropout DH, flip chip - Maestro 3, 12x157mm thru-axle, 27.5 or 29-inch rear wheel compatible
FORK	Fox 40 Factory, GRIP2 damper, 203mm, 20x110, custom tuned for Giant
SHOCK	Fox DHX2 Factory, SLS coil, 225/75, custom tuned for Giant S/M #425, M/L #450, L/XL #475
COMPONENTS	
HANDLEBAR	Giant Contact SL TR35, composite
GRIPS	Giant Tactal Pro Single
STEM	TruVativ Descendant Direct Mount, 35
SEATPOST	Giant Contact, 30.9mm, 0 offset, 400mm
SADDLE	Giant Romero
DRIVETRAIN	
SHIFTERS	SRAM GX Eagle DH
FRONT DERAILLEUR	N/A
REAR DERAILLEUR	SRAM GX Eagle DH
BRAKES	Shimano Saint M-820, hydraulic, Shimano RT-66 rotors, [F]220mm, [R]203mm
BRAKE LEVERS	Shimano Saint BL-M820
CASSETTE	SRAM GX DH
CHAIN	SRAM PC 1110
CRANKSET	TruVativ Descendant DH, 34t, 56.5mm chainline
BOTTOM BRACKET	SRAM DUB, threaded, 83mm

WHEELS	
RIMS	Giant AM30, alloy, 28-hole, 30mm inner width
HUBS	[F] alloy, sealed cartridge, 6-bolt, 20x110mm [R] alloy, 72t pawl driver, sealed cartridge, 6-bolt, 12x157mm
SPOKES	Sapim Laser, straight pull, DBL
TIRES	[F] Maxxis Assegai 29x2.5 WT, 3C MaxxGrip, DH, TR [R] Maxxis Minion DHR II 27.5x2.4 WT, 3C, MaxxGrip, DH, TR tubeless
EXTRAS	Tubeless prepared, 2.5" max tire size, 36t max chainring size, MRP SXg chain guide, full downtube protector. *Not compatible with 2023 or earlier RockShox BoXXer Ultimate or BoXXer Select

Price: \$11,499.00

GEOMETRY

FRAME	S/M			M/L			L/XL		
	LOW	MID	HIGH	LOW	MID	HIGH	LOW	MID	HIGH
Seat Tube Length (mm)	430			450			450		
Seat Post Insertion Depth (mm)	155			165			165		
Seat Tube Angle	78.4° 78.7° 79.1°			78.4° 78.8° 79.1°			78.5° 78.8° 79.1°		
Top Tube Length (mm)	571.2 570.5 569.8			591.3 590.5 589.8			611.3 610.6 609.8		
Head Tube Length (mm)	110			110			110		
Head Tube Angle	61.6° 61.9° 62.3°			61.6° 62.0° 62.3°			61.7° 62.0° 62.3°		
Fork Rake (mm)	52			52			52		
Trail (mm)	146.4 143.6 140.8			146.2 143.5 140.8			146 143.3 140.8		
Wheelbase (mm)	1273 1271.9 1270.6			1293 1291.8 1290.6			1313 1311.9 1310.6		
Chain Stay Length (mm)	447.9 446.5 445			447.9 446.5 445			447.9 446.5 445		
Bottom Bracket Drop (mm)	13.1 8.1 3			13.3 8.3 3.1			13.5 8.4 3.2		
Stack (mm)	634.6 631.9 629.1			634.9 632.2 629.2			635.3 632.4 629.3		
Reach (mm)	440.9 444.7 448.6			461.2 464.9 468.6			481.5 485.1 488.6		
Stand Over Height (mm)	733.7 738.2 742.9			735.2 740 744.8			742.9 747.6 752.3		
Stem Length (mm)	50			50			50		
Crank Length (mm)	165			165			165		
Wheel Size	[R] 27.5" / [F] 29"			[R] 27.5" / [F] 29"			[R] 27.5" / [F] 29"		

Please note that our specifications may be impacted by running substitution changes, we highly recommend confirming the specifications of our products with your local retailer at the time of sale if purchasing in-store. *Recommended Retail Prices are