

GLORY ADVANCED

GIANT



SPECS

FRAME	
SIZES	S/M, M/L, L/XL
COLOURS	Moon Dust
FRAME	Advanced-grade composite front and rear triangles, 200mm Maestro suspension, flip chip - headset, flip chip - dropout DH, flip chip - Maestro 3, 12x157mm thru-axle, 27.5 or 29-inch rear wheel compatible
FORK	Fox 40 Factory, GRIP X2 damper, 203mm, 20x110
SHOCK	Fox DHX2 Factory, SLS coil, 225/75 S/M:425#, M/L:450#, L/XL:475#
COMPONENTS	
HANDLEBAR	Giant Contact SL TR35, 800x35mm, 20mm rise
GRIPS	Giant Tactal Pro Single
STEM	TruVativ Descendant Direct Mount 35 S/M:50mm, M/L:50mm, L/XL:50mm
SEATPOST	Giant Contact, 30.9mm, 0 offset, 400mm
SADDLE	Giant Romero
PEDALS	platform [GC,GT]
DRIVETRAIN	
SHIFTERS	TRP EVO 7 DH, 1x7
FRONT DERAILLEUR	N/A
REAR DERAILLEUR	TRP EVO 7 DH
BRAKES	TRP EVO Pro, hydraulic, TRP rotors [F]220mm, [R]203mm
BRAKE LEVERS	TRP EVO Pro
CASSETTE	TRP EVO 7 DH, 11-24
CHAIN	KMC X-11
CRANKSET	TRP EVO 7 DH, 34t, 56.5mm chainline S/M:165mm, M/L:165mm, L/XL:165mm
BOTTOM BRACKET	TRP, threaded, 83mm

WHEELS	
RIMS	Giant TRA 2 rims, 6061 alloy, hookless, 30mm inner width, 40mm outer width, 21mm height, Wide Guard Technology
HUBS	[F] Giant MTB alloy, 6-bolt [R] Giant MTB alloy, 30t 3-pawl driver, 6-bolt
SPOKES	Stainless steel
TIRES	[F] Maxxis Assegai 29x2.5 WT, 3C MaxxGrip, DH, TR [R] Maxxis Minion DHR II 27.5x2.4 WT, 3C, MaxxGrip, DH, TR tubeless
EXTRAS	tubeless prepared, 2.5" max tire size, 36t max chainring size, MRP SXg chain guide, full down tube protector

Suggested Retail Price (CDN): \$8,999.00

FRAME GEOMETRY

FRAME	S/M	L/XL	M/L
	LOW MID HIGH	LOW MID HIGH	LOW MID HIGH
Seat Tube Length (mm)	430	450	450
Seat Post Insertion Depth (mm)	155	165	165
Seat Tube Angle	78.4° 78.7° 79.1°	78.5° 78.8° 79.1°	78.4° 78.8° 79.1°
Top Tube Length (mm)	571 571 570	611 611 610	591 591 590
Head Tube Length (mm)	110	110	110
Head Tube Angle	61.6° 61.9° 62.3°	61.7° 62.0° 62.3°	61.6° 62.0° 62.3°
Fork Rake (mm)	52	52	52
Trail (mm)	146.4 143.6 140.8	146 143.3 140.8	146.2 143.5 140.8
Wheelbase (mm)	1273 1272 1271	1313 1312 1311	1293 1292 1291
Chain Stay Length (mm)	448 447 445	448 447 445	448 447 445
Bottom Bracket Drop (mm)	13 8 3	14 8 3	13 8 3
Stack (mm)	635 632 629	635 632 629	635 632 629
Reach (mm)	441 445 449	482 485 489	461 465 469
Stand Over Height (mm)	734 738 743	743 748 752	735 740 745
Handlebar Width (mm)	800	800	800
Stem Length (mm)	50	50	50
Crank Length (mm)	165	165	165

All prices and specifications are subject to change without notice.