

GLORY ADVANCED

GIANT



ESPECIFICACIONES

CUADRO	
TALLAS	S/M, M/L, L/XL
COLORES	Shoreline/Carbon
CUADRO	Advanced-grade composite front and rear triangles, 200mm Maestro suspension, flip chip - headset, flip chip - dropout DH, flip chip - Maestro 3, 12x157mm thru-axle, 27.5 or 29-inch rear wheel compatible
TIJERA	Fox 40 Factory, GRIP2 damper, 203mm, 20x110, custom tuned for Giant
AMORTIGUADOR	Fox DHX2 Factory, SLS coil, 225/75, custom tuned for Giant S/M #425, M/L #450, L/XL #475
COMPONENTES	
MANUBRIO	Giant Contact SL TR35, composite, 800x35mm, 20mm rise
GRIPS	Giant Tactal Pro Single
POTENCIA	TruVativ Descendant Direct Mount, 35 S/M:50mm, M/L:50mm, L/XL:50mm
POSTE DE ASIENTO	Giant Contact, 30.9mm, 0 offset, 400mm
ASIENTO	Giant Romero
TRANSMISIÓN	
MANETAS DE CAMBIO	SRAM GX Eagle DH, 1x7
DESVIADOR	N/A
CAMBIO TRASERO	SRAM GX Eagle DH
FRENOS	Shimano Saint M-820, hydraulic, Shimano RT-66 rotors, [F]220mm, [R]203mm
PALANCAS DE FRENOS	Shimano Saint BL-M820
CASSETTE	SRAM GX DH, 11-25
CADENA	SRAM PC 1110
MULTIPLICACIÓN	TruVativ Descendant DH, 34t, 56.5mm chainline, S/M:165mm, M/L:170mm, L/XL:170mm
EJE DE CENTRO	SRAM DUB, threaded, 83mm

RUEDAS	
RUEDAS	Giant AM30, alloy, 28-hole, 30mm inner width
MAZAS	[F] alloy, sealed cartridge, 6-bolt, 20x110mm [R] alloy, 72t pawl driver, sealed cartridge, 6-bolt, 12x157mm
RAYOS	Sapim Laser, straight pull, DBL
NEUMÁTICOS	[F] Maxxis Assegai 29x2.5 WT, 3C MaxxGrip, DH, TR [R] Maxxis Minion DHR II 27.5x2.4 WT, 3C, MaxxGrip, DH, TR tubeless
EXTRAS	tubeless prepared, 2.5" max tire size, 36t max chainring size, MRP SXg chain guide, full downtube protector. *Not compatible with 2023 or earlier RockShox BoXXer Ultimate or BoXXer Select

Precio: \$169,900.00

GEOMETRÍA

CUADRO	S/M			M/L			L/XL		
	LOW	MID	HIGH	LOW	MID	HIGH	LOW	MID	HIGH
Longitud de la Base del Poste de Asiento (mm)	430			450			450		
Seat Post Insertion Depth (mm)	155			165			165		
Ángulo de la Base del Poste de Asiento	78.4°	78.7°	79.1°	78.4°	78.8°	79.1°	78.5°	78.8°	79.1°
Longitud del Tubo Superior (mm)	571.2	570.5	569.8	591.3	590.5	589.8	611.3	610.6	609.9
Longitud del Telescopio (mm)	110			110			110		
Ángulo del Telescopio	61.6°	61.9°	62.3°	61.6°	62.0°	62.3°	61.7°	62.0°	62.3°
Rake (mm)	52			52			52		
Trail (mm)	146.4	143.6	140.8	146.2	143.5	140.8	146	143.3	140.5
Distancia entre Ejes (mm)	1273	1271.9	1270.6	1293	1291.8	1290.6	1313	1311.9	1310.6
Longitud de Vaina Inferior (mm)	447.9	446.5	445	447.9	446.5	445	447.9	446.5	445
Caída del Eje de Centro (mm)	13.1	8.1	3	13.3	8.3	3.1	13.5	8.4	3.2
Stack (mm)	634.6	631.9	629.1	634.9	632.2	629.2	635.3	632.4	629.5
Reach (mm)	440.9	444.7	448.6	461.2	464.9	468.6	481.5	485.1	488.8
Altura del Tubo Superior al Suelo (mm)	733.7	738.2	742.9	735.2	740	744.8	742.9	747.6	751.3
Ancho del Manubrio (mm)	800			800			800		
Longitud de la Potencia (mm)	50			50			50		
Longitud de la Biela (mm)	165			165			165		
Tamaño de las Ruedas	[R] 27.5" / [F] 29"			[R] 27.5" / [F] 29"			[R] 27.5" / [F] 29"		

Todas las especificaciones están sujetas a cambios sin previo aviso.