

GLORY ADVANCED



TEKNISET TIEDOT

RUNKO	
KOOT	S/M, M/L, L/XL
VÄRIT	Black Lava/Mercury/Chrome
RUNKO	Advanced-grade composite front and rear triangles, 200mm Maestro suspension, flip chip - headset, flip chip - dropout DH, flip chip - Maestro 3, 12x157mm thru-axle, 27.5 or 29-inch rear wheel compatible
HAARUKKA	Fox 40 Factory, GRIP X2 damper, 203mm, 20x110
ISKUNVAIMENNIN	Fox DHX2 Factory, SLS coil, 225/75, custom tuned for Giant S/M:425#, M/L:450#, L/XL:475#
KOMONENTIT	
OHJAUSTANKO	Giant Contact SL TR35, 800x35mm, 20mm rise
GRIPIT	Giant Tactal Pro Single
OHJAINKANNATIN	TruVativ Descendant Direct Mount 35 S/M:50mm, M/L:50mm, L/XL:50mm
SATULATOLPPA	Giant Contact, 30.9mm, 0 offset, 400mm
SATULA	Giant Romero
VOIMANSIIRTO	
VAIHDEVIPU	SRAM GX Eagle DH, 1x7
ETUVAIHTAJA	N/A
TAKAVAIHTAJA	SRAM GX Eagle DH
JARRUT	Shimano Saint M-820, hydraulic, Shimano RT-66 rotors [F]220mm, [R]203mm
JARRUKAHVAT	Shimano Saint BL-M820
RATASPAKKA	SRAM GX DH, 11-25
KETJUT	SRAM PC 1110
KAMPISARJA	TruVativ Descendent DH, 34t, 56.5mm chainline S/M:165mm, M/L:170mm, L/XL:170mm
KESKIÖ	SRAM DUB, threaded, 83mm

RENKAAT	
VANTEET	Giant TRA 2 rims, 6061 alloy, hookless, 30mm inner width, 40mm outer width, 21mm height, Wide Guard Technology
NAVAT	[F] Giant MTB alloy, 6-bolt, [R] Giant MTB alloy, 30t 3-pawl driver, 6-bolt
PINNAT	Stainless steel
RENKAAT	[F] Maxxis Assegai 29x2.5 WT, 3C MaxxGrip, DH, TR [R] Maxxis Minion DHR II 27.5x2.4 WT, 3C, MaxxGrip, DH, TR tubeless
LISÄTIEDOT	tubeless prepared, 2.5" max tire size, 36t max chainring size, MRP SXg chain guide, full down tube protector

Suositushinta: 8 499,00 €

GEOMETRIA

RUNKO	M/L	L/XL
	LOW MID HIGH	LOW MID HIGH
Satulaputken pituus (mm)	450	450
Satulatolpan asennussyvyys (mm)	165	165
Satulaputken kulma	78,4° 78,8° 79,1°	78,5° 78,8° 79,1°
Vaakaputken pituus (mm)	591,3 590,5 589,8	611,3 610,6 609,8
Emäputken pituus (mm)	110	110
Emäputken kulma	61,6° 62,0° 62,3°	61,7° 62,0° 62,3°
Haarukan offset (mm)	52	52
Trail-mitta (mm)	146,2 143,5 140,8	146 143,3 140,8
Akseliväli (mm)	1293 1291,8 1290,6	1313 1311,9 1310,6
Takahaarukan alaputken pituus (mm)	447,9 446,5 445	447,9 446,5 445
Keskiön pudotus (mm)	13,3 8,3 3,1	13,5 8,4 3,2
Stack-mitta (mm)	634,9 632,2 629,2	635,3 632,4 629,3
Reach-mitta (mm)	461,2 464,9 468,6	481,5 485,1 488,6
Standover-mitta (mm)	735,2 740 744,8	742,9 747,6 752,3
Ohjaustangon leveys (mm)	800	800
Ohjainkannattimen pituus (mm)	50	50
Kammen pituus (mm)	165	165
Rengaskoko	[R] 27.5" / [F] 29"	[R] 27.5" / [F] 29"

Kaikki ilmoitetut tekniset tiedot voivat muuttua ilman erillistä ilmoitusta.