GLORY ADVANCED



TEKNISET TIEDOT

RUNKO	
KOOT	S/M, M/L, L/XL
VÄRIT	Moon Dust
RUNKO	Advanced-grade composite front and rear triangles, 200mm Maestro suspension, flip chip - headset, flip chip - dropout DH, flip chip - Maestro 3, 12x157mm thru-axle, 27.5 or 29-inch rear wheel compatible
HAARUKKA	Fox 40 Factory, GRIP X2 damper, 203mm, 20x110
ISKUNVAIMENNIN	Fox DHX2 Factory, SLS coil, 225/75 S/M:425#, M/L:450#, L/XL:475#
KOMPONENTIT	
OHJAUSTANKO	Giant Contact SL TR35, 800x35mm, 20mm rise
GRIPIT	Giant Tactal Pro Single
OHJAINKANNATIN	TruVativ Descendant Direct Mount 35 S/M:50mm, M/L:50mm, L/XL:50mm
SATULATOLPPA	Giant Contact, 30.9mm, 0 offset, 400mm
SATULA	Giant Romero
POLKIMET	platform [GC,GT]
VOIMANSIIRTO	
VAIHDEVIPU	TRP EVO 7 DH, 1x7
ETUVAIHTAJA	N/A
TAKAVAIHTAJA	TRP EVO 7 DH
JARRUT	TRP EVO Pro, hydraulic, TRP rotors [F]220mm, [R]203mm
JARRUKAHVAT	TRP EVO Pro
RATASPAKKA	TRP EVO 7 DH, 11-24
KETJUT	KMC X-11
KAMPISARJA	TRP EVO 7 DH, 34t, 56.5mm chainline S/M:165mm, M/L:165mm, L/XL:165mm
KESKIÖ	TRP, threaded, 83mm

RENKAAT	
VANTEET	Giant TRA 2 rims, 6061 alloy, hookless, 30mm inner width, 40mm outer width, 21mm height, Wide Guard Technology
NAVAT	[F] Giant MTB alloy, 6-bolt [R] Giant MTB alloy, 30t 3-pawl driver, 6-bolt
PINNAT	Stainless steel
RENKAAT	[F] Maxxis Assegai 29x2.5 WT, 3C MaxxGrip, DH, TR [R] Maxxis Minion DHR II 27.5x2.4 WT, 3C, MaxxGrip, DH, TR tubeless
LISÄTIEDOT	tubeless prepared, 2.5" max tire size, 36t max chainring size, MRP SXg chain guide, full down tube protector

Suositushinta: 8 499,00 €

GEOMETRIA

RUNKO	L/XL	M/L
	LOW | MID | HIGH	LOW | MID | HIGH
Satulaputken pituus (mm)	450	450
Satulatolpan asennussyvyys (mm)	165	165
Satulaputken kulma	78,5° | 78,8° | 79,1°	78,4° | 78,8° | 79,1°
Vaakaputken pituus (mm)	611 | 611 | 610	591 | 591 | 590
Emäputken pituus (mm)	110	110
Emäputken kulma	61,7° | 62,0° | 62,3°	61,6° | 62,0° | 62,3°
Haarukan offset (mm)	52	52
Trail-mitta (mm)	146 | 143,3 | 140,8	146,2 | 143,5 | 140,8
Akseliväli (mm)	1313 | 1312 | 1311	1293 | 1292 | 1291
Takahaarukan alaputken pituus (mm)	448 | 447 | 445	448 | 447 | 445
Keskiön pudotus (mm)	14 | 8 | 3	13 | 8 | 3
Stack-mitta (mm)	635 | 632 | 629	635 | 632 | 629
Reach-mitta (mm)	482 | 485 | 489	461 | 465 | 469
Standover-mitta (mm)	743 | 748 | 752	735 | 740 | 745
Ohjaustangon leveys (mm)	800	800
Ohjainkannattimen pituus (mm)	50	50
Kammen pituus (mm)	165	165

Kaikki ilmoitetut tekniset tiedot voivat muuttua ilman erillistä ilmoitusta.