

GLORY ADVANCED



SPECIFICATIES

FRAME	
MATEN	M, L
KLEUREN	Black Lava/Mercury/Chrome
FRAME	Advanced-grade composite front and rear triangles, 200mm Maestro suspension, flip chip - headset, flip chip - dropout DH, flip chip - Maestro 3, 12x157mm thru-axle, 27.5 or 29-inch rear wheel compatible
VOORVORK	Fox 40 Factory, GRIP X2 damper, 203mm, 20x110
DEMPER	Fox DHX2 Factory, SLS coil, 225/75, custom tuned for Giant S/M:425#, M/L:450#, L/XL:475#
ONDERDELEN	
STUUR	Giant Contact SL TR35, 800x35mm, 20mm rise
HANDVATTEN	Giant Tactal Pro Single
STUURPEN	TruVativ Descendant Direct Mount 35 S/M:50mm, M/L:50mm, L/XL:50mm
ZADELPEN	Giant Contact, 30.9mm, 0 offset, 400mm
ZADEL	Giant Romero
AFMONTAGE	
SHIFTERS	SRAM GX Eagle DH, 1x7
VOORDERAILLEUR	N/A
ACHTTERDERAILLEUR	SRAM GX Eagle DH
REMMEN	Shimano Saint M-820, hydraulic, Shimano RT-66 rotors [F]220mm, [R]203mm
REMHEDELS	Shimano Saint BL-M820
CASSETTE	SRAM GX DH, 11-25
AANDRIJVING	SRAM PC 1110
CRANKSET	TruVativ Descendent DH, 34t, 56.5mm chainline S/M:165mm, M/L:170mm, L/XL:170mm
BOTTOM BRACKET	SRAM DUB, threaded, 83mm

WIELSET	
VELGEN	Giant TRA 2 rims, 6061 alloy, hookless, 30mm inner width, 40mm outer width, 21mm height, Wide Guard Technology
NAVEN	[F] Giant MTB alloy, 6-bolt, [R] Giant MTB alloy, 30t 3-pawl driver, 6-bolt
SPAKEN	Stainless steel
BANDEN	[F] Maxxis Assegai 29x2.5 WT, 3C MaxxGrip, DH, TR [R] Maxxis Minion DHR II 27.5x2.4 WT, 3C, MaxxGrip, DH, TR tubeless
EXTRA'S	tubeless prepared, 2.5" max tire size, 36t max chainring size, MRP SXg chain guide, full down tube protector

Adviesprijs: € 7.999,00

GEOMETRIE

FRAME	M/L	L/XL
	LOW MID HIGH	LOW MID HIGH
Zitbuis Lengte (mm)	450	450
Seat Post Insertion Depth (mm)	165	165
Zitbuis Hoek	78,4° 78,8° 79,1°	78,5° 78,8° 79,1°
Frame Lengte (horizontaal) (mm)	591,3 590,5 589,8	611,3 610,6 609,8
Balhoofdbuis Lengte (mm)	110	110
Balhoofdbuis Hoek	61,6° 62,0° 62,3°	61,7° 62,0° 62,3°
Vork Sprong (mm)	52	52
Naloop (mm)	146,2 143,5 140,8	146 143,3 140,8
Wielbasis (mm)	1293 1291,8 1290,6	1313 1311,9 1310,6
Liggende achtervork lengte (mm)	447,9 446,5 445	447,9 446,5 445
Bottom Bracket Drop (mm)	13,3 8,3 3,1	13,5 8,4 3,2
Stack (mm)	634,9 632,2 629,2	635,3 632,4 629,3
Reach (mm)	461,2 464,9 468,6	481,5 485,1 488,6
Stand Over Height (mm)	735,2 740 744,8	742,9 747,6 752,3
Stuur breedte (mm)	800	800
Stuurpen Lengte (mm)	50	50
Cranklengte (mm)	165	165
Wielmaat	[R] 27.5" / [F] 29"	[R] 27.5" / [F] 29"

Deze specificaties zijn met de grootste zorgvuldigheid samengesteld. Specificaties, beschikbaarheid, prijzen en kleuren kunnen echter zonder voor aankondiging wijzigen.