

GLORY ADVANCED FRAMESET

GIANT



SPECIFIKACE

| RÁM | |
|-----------|--|
| VELIKOSTI | S/M, M/L, L/XL |
| BARVA | Quarry/Chrome |
| RÁM | Advanced-grade composite front and rear triangles, 200mm Maestro suspension, flip chip - headset, flip chip - dropout DH, flip chip - Maestro 3, 12x157mm thru-axle, 27.5 or 29-inch rear wheel compatible |
| TLUMIČ | Fox DHX2 Factory, SLS coil, 225/75, custom tuned for Giant S/M:425, M/L:450, L/XL:475 |

| KOLA | |
|---------|--|
| DOPLŇKY | 2.5" max tire size, 36t max chainring size, full down tube protector |

Cena: 144 999 Kč

GEOMETRIE

| RÁM | S/M | | | M/L | | | L/XL | | |
|-----------------------------|------------------------|-----|------|------------------------|-----|------|------------------------|-----|------|
| | LOW | MID | HIGH | LOW | MID | HIGH | LOW | MID | HIGH |
| Délka sedlové trubky (mm) | 430 | | | 450 | | | 450 | | |
| Max. zasunutí sedlovky (mm) | 155 | | | 165 | | | 165 | | |
| Úhel sedlové trubky | 78,4° 78,7° 79,1° | | | 78,4° 78,8° 79,1° | | | 78,5° 78,8° 79,1° | | |
| Délka horní trubky (mm) | 571,2 570,5 569,8 | | | 591,3 590,5 589,8 | | | 611,3 610,6 609,8 | | |
| Délka hlavové trubky (mm) | 110 | | | 110 | | | 110 | | |
| Úhel hlavové trubky | 61,6° 61,9° 62,3° | | | 61,6° 62,0° 62,3° | | | 61,7° 62,0° 62,3° | | |
| Offset vidlice (mm) | 52 | | | 52 | | | 52 | | |
| Trail (mm) | 146,4 143,6 140,8 | | | 146,2 143,5 140,8 | | | 146 143,3 140,8 | | |
| Rozvor (mm) | 1273 1271,9 1270,6 | | | 1293 1291,8 1290,6 | | | 1313 1311,9 1310,6 | | |
| Délka řetězové vzpěry (mm) | 447,9 446,5 445 | | | 447,9 446,5 445 | | | 447,9 446,5 445 | | |
| Bottom Bracket Drop (mm) | 13,1 8,1 3 | | | 13,3 8,3 3,1 | | | 13,5 8,4 3,2 | | |
| Stack (mm) | 634,6 631,9 629,1 | | | 634,9 632,2 629,2 | | | 635,3 632,4 629,3 | | |
| Reach (mm) | 440,9 444,7 448,6 | | | 461,2 464,9 468,6 | | | 481,5 485,1 488,6 | | |
| Výška rámu od země (mm) | 733,7 738,2 742,9 | | | 735,2 740 744,8 | | | 742,9 747,6 752,3 | | |
| Šířka řídicí (mm) | 800 | | | 800 | | | 800 | | |
| Délka představce (mm) | 50 | | | 50 | | | 50 | | |
| Délka klíků (mm) | 165 | | | 165 | | | 165 | | |
| Rozměr kol | [R] 27.5" / [F] 29" | | | [R] 27.5" / [F] 29" | | | [R] 27.5" / [F] 29" | | |

Děláme vše pro to, aby veškeré údaje na tomto webu byly správné a aktuální. Přesto si ale musíme vyhradit právo na případné změny specifikací, barevného provedení a cen, a to bez předchozího upozornění. Děkujeme za pochopení.