



SPECIFIKACIJE

OKVIR	
VELIČINE	S/M, M/L, L/XL
BOJE	Shoreline/Carbon
OKVIR	Advanced-grade composite front and rear triangles, 200mm Maestro suspension, flip chip - headset, flip chip - dropout DH, flip chip - Maestro 3, 12x157mm thru-axle, 27.5 or 29-inch rear wheel compatible
VILICA	Fox 40 Factory, GRIP2 damper, 203mm, 20x110, custom tuned for Giant
AMORTIZER	Fox DHX2 Factory, SLS coil, 225/75, custom tuned for Giant S/M #425, M/L #450, L/XL #475
KOMPONENTE	
VOLAN	Giant Contact SL TR35, composite, 800x35mm, 20mm rise
GRIPS	Giant Tactal Pro Single
LULA VOLANA	TruVativ Descendant Direct Mount, 35 S/M:50mm, M/L:50mm, L/XL:50mm
CIJEV SJEDALA	Giant Contact, 30.9mm, 0 offset, 400mm
SJEDALO	Giant Romero
POGON	
RUČICE MJENJAČA	SRAM GX Eagle DH, 1x7
PREDNJI MJENJAČ	N/A
STRAŽNJI MJENJAČ	SRAM GX Eagle DH
KOČNICE	Shimano Saint M-820, hydraulic, Shimano RT-66 rotors, [F]220mm, [R]203mm
RUČICE KOČNICA	Shimano Saint BL-M820
KAZETA	SRAM GX DH, 11-25
LANAC	SRAM PC 1110
POGON	TruVativ Descendent DH, 34t, 56.5mm chainline, S/M:165mm, M/L:170mm, L/XL:170mm
OSOVINA POGONA (BB)	SRAM DUB, threaded, 83mm

KOTAČI	
OBRUČI	Giant AM30, alloy, 28-hole, 30mm inner width
NABE	[F] alloy, sealed cartridge, 6-bolt, 20x110mm [R] alloy, 72t pawl driver, sealed cartridge, 6-bolt, 12x157mm
ŽBICE	Sapim Laser, straight pull, DBL
GUME	[F] Maxxis Assegai 29x2.5 WT, 3C MaxxGrip, DH, TR [R] Maxxis Minion DHR II 27.5x2.4 WT, 3C, MaxxGrip, DH, TR tubeless
DODACI	tubeless prepared, 2.5" max tire size, 36t max chainring size, MRP SXg chain guide, full downtube protector. *Not compatible with 2023 or earlier RockShox BoXXer Ultimate or BoXXer Select

GEOMETRIJA

OKVIR	S/M			M/L		
	LOW	MID	HIGH	LOW	MID	HIGH
Dužina cijevi sjedala (mm)	430			450		
Seat Post Insertion Depth (mm)	155			165		
Kut cijevi sjedala	78,4° 78,7° 79,1°			78,4° 78,8° 79,2°		
Dužina gornje cijevi (mm)	571,2 570,5 569,8			591,3 590,5 589,7		
Dužina prednje cijevi (mm)	110			110		
Kut vilice	61,6° 61,9° 62,3°			61,6° 62,0° 62,3°		
Zakrivljenost vilice (offset) (mm)	52			52		
Staza (mm)	146,4 143,6 140,8			146,2 143,5 140,8		
Međuosovinski razmak kotača (mm)	1273 1271,9 1270,6			1293 1291,8 1290,5		
Dužina od osovine pogona do osovine zadnjeg kotača (CS) (mm)	447,9 446,5 445			447,9 446,5 445		
Položaj osovine pogona (mm)	13,1 8,1 3			13,3 8,3 3,1		
Vertikalna dužina od osovine pogona do glave okvira (stack) (mm)	634,6 631,9 629,1			634,9 632,2 629,5		
Horizontalna dužina od osovine pogona do glave okvira (reach) (mm)	440,9 444,7 448,6			461,2 464,9 468,6		
Prekoračna visina (mm)	733,7 738,2 742,9			735,2 740 744,8		
Širina volana (mm)	800			800		
Dužina lule volana (mm)	50			50		
Dužina poluge pedale (mm)	165			165		
Veličina kotača	[R] 27.5" / [F] 29"			[R] 27.5" / [F] 29"		

Sve navedene specifikacije podložne su promjeni bez prethodne najave.