

GLORY ADVANCED LEGENDS EDITION  
FRAMESET

GIANT



SPECS

| FRAME   |                                                                                                                                                                                                            |
|---------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| SIZES   | S/M, M/L, L/XL                                                                                                                                                                                             |
| COLOURS | Legends Edition                                                                                                                                                                                            |
| FRAME   | Advanced-grade composite front and rear triangles, 200mm Maestro suspension, flip chip - headset, flip chip - dropout DH, flip chip - Maestro 3, 12x157mm thru-axle, 27.5 or 29-inch rear wheel compatible |
| FORK    | Fox 40 Factory, GRIP2 damper, 203mm, 20x110, custom tuned for Giant                                                                                                                                        |
| SHOCK   | Fox DHX2 Factory, SLS coil, 225/75, custom tuned for Giant S/M 425, M/L 450, L/XL 475                                                                                                                      |

| WHEELS |                                                                                                                                                                                             |
|--------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| EXTRAS | Tubeless prepared, 2.5" max tire size, 36t max chainring size, MRP SXg chain guide, full downtube protector. *Not compatible with 2023 or earlier RockShox BoXXer Ultimate or BoXXer Select |

Price: \$8,999.00

GEOMETRY

| FRAME                          | S/M                 |        |        | M/L                 |        |        | L/XL                |        |        |
|--------------------------------|---------------------|--------|--------|---------------------|--------|--------|---------------------|--------|--------|
|                                | LOW                 | MID    | HIGH   | LOW                 | MID    | HIGH   | LOW                 | MID    | HIGH   |
| Seat Tube Length (mm)          | 430                 |        |        | 450                 |        |        | 450                 |        |        |
| Seat Post Insertion Depth (mm) | 155                 |        |        | 165                 |        |        | 165                 |        |        |
| Seat Tube Angle                | 78.4°               | 78.7°  | 79.1°  | 78.4°               | 78.8°  | 79.1°  | 78.5°               | 78.8°  | 79.1°  |
| Top Tube Length (mm)           | 571.2               | 570.5  | 569.8  | 591.3               | 590.5  | 589.8  | 611.3               | 610.6  | 609.8  |
| Head Tube Length (mm)          | 110                 |        |        | 110                 |        |        | 110                 |        |        |
| Head Tube Angle                | 61.6°               | 61.9°  | 62.3°  | 61.6°               | 62.0°  | 62.3°  | 61.7°               | 62.0°  | 62.3°  |
| Fork Rake (mm)                 | 52                  |        |        | 52                  |        |        | 52                  |        |        |
| Trail (mm)                     | 146.4               | 143.6  | 140.8  | 146.2               | 143.5  | 140.8  | 146                 | 143.3  | 140.8  |
| Wheelbase (mm)                 | 1273                | 1271.9 | 1270.6 | 1293                | 1291.8 | 1290.6 | 1313                | 1311.9 | 1310.6 |
| Chain Stay Length (mm)         | 447.9               | 446.5  | 445    | 447.9               | 446.5  | 445    | 447.9               | 446.5  | 445    |
| Bottom Bracket Drop (mm)       | 13.1                | 8.1    | 3      | 13.3                | 8.3    | 3.1    | 13.5                | 8.4    | 3.2    |
| Stack (mm)                     | 634.6               | 631.9  | 629.1  | 634.9               | 632.2  | 629.2  | 635.3               | 632.4  | 629.3  |
| Reach (mm)                     | 440.9               | 444.7  | 448.6  | 461.2               | 464.9  | 468.6  | 481.5               | 485.1  | 488.6  |
| Stand Over Height (mm)         | 733.7               | 738.2  | 742.9  | 735.2               | 740    | 744.8  | 742.9               | 747.6  | 752.3  |
| Stem Length (mm)               | 50                  |        |        | 50                  |        |        | 50                  |        |        |
| Crank Length (mm)              | 165                 |        |        | 165                 |        |        | 165                 |        |        |
| Wheel Size                     | [R] 27.5" / [F] 29" |        |        | [R] 27.5" / [F] 29" |        |        | [R] 27.5" / [F] 29" |        |        |

Please note that our specifications may be impacted by running substitution changes, we highly recommend confirming the specifications of our products with your local retailer at the time of sale if purchasing in-store. \*Recommended Retail Prices are subject to change without notice and may vary from store to store depending on freight and assembly costs.