GLORY ADVANCED



SPECIFICATIES

FRAME	
MATEN	S/M, M/L, L/XL
KLEUREN	Moon Dust
FRAME	Advanced-grade composite front and rear triangles, 200mm Maestro suspension, flip chip - headset, flip chip - dropout DH, flip chip - Maestro 3, 12x157mm thru-axle, 27.5 or 29-inch rear wheel compatible
VOORVORK	Fox 40 Factory, GRIP X2 damper, 203mm, 20x110
DEMPER	Fox DHX2 Factory, SLS coil, 225/75 S/M:425#, M/L:450#, L/XL:475#
ONDERDELEN	
STUUR	Giant Contact SL TR35, 800x35mm, 20mm rise
HANDVATTEN	Giant Tactal Pro Single
STUURPEN	TruVativ Descendant Direct Mount 35 S/M:50mm, M/L:50mm, L/XL:50mm
ZADELPEN	Giant Contact, 30.9mm, 0 offset, 400mm
ZADEL	Giant Romero
PEDALEN	platform [GC,GT]
AFMONTAGE	
SHIFTERS	TRP EVO 7 DH, 1x7
VOORDERAILLEUR	N/A
ACHTERDERAILLEUR	TRP EVO 7 DH
REMMEN	TRP EVO Pro, hydraulic, TRP rotors [F]220mm, [R]203mm
REMHENDELS	TRP EVO Pro
CASSETTE	TRP EVO 7 DH, 11-24
AANDRIJVING	KMC X-11
CRANKSET	TRP EVO 7 DH, 34t, 56.5mm chainline S/M:165mm, M/L:165mm, L/XL:165mm
BOTTOM BRACKET	TRP, threaded, 83mm

WIELSET	
VELGEN	Giant TRA 2 rims, 6061 alloy, hookless, 30mm inner width, 40mm outer width, 21mm height, Wide Guard Technology
NAVEN	[F] Giant MTB alloy, 6-bolt [R] Giant MTB alloy, 30t 3-pawl driver, 6-bolt
SPAKEN	Stainless steel
BANDEN	[F] Maxxis Assegai 29x2.5 WT, 3C MaxxGrip, DH, TR [R] Maxxis Minion DHR II 27.5x2.4 WT, 3C, MaxxGrip, DH, TR tubeless
EXTRA'S	tubeless prepared, 2.5" max tire size, 36t max chainring size, MRP SXg chain guide, full down tube protector

Adviesprijs: € 7.999,00

GEOMETRIE

FRAME	L/XL	M/L
	LOW | MID | HIGH	LOW | MID | HIGH
Zitbuis Lengte (mm)	450	450
Seat Post Insertion Depth (mm)	165	165
Zitbuis Hoek	78,5° | 78,8° | 79,1°	78,4° | 78,8° | 79,1°
Frame Lengte (horizontaal) (mm)	611 | 611 | 610	591 | 591 | 590
Balhoofdbuis Lengte (mm)	110	110
Balhoofdbuis Hoek	61,7° | 62,0° | 62,3°	61,6° | 62,0° | 62,3°
Vork Sprong (mm)	52	52
Naloop (mm)	146 | 143,3 | 140,8	146,2 | 143,5 | 140,8
Wielbasis (mm)	1313 | 1312 | 1311	1293 | 1292 | 1291
Liggende achtervork lengte (mm)	448 | 447 | 445	448 | 447 | 445
Bottom Bracket Drop (mm)	14 | 8 | 3	13 | 8 | 3
Stack (mm)	635 | 632 | 629	635 | 632 | 629
Reach (mm)	482 | 485 | 489	461 | 465 | 469
Stand Over Height (mm)	743 | 748 | 752	735 | 740 | 745
Stuur breedte (mm)	800	800
Stuurpen Lengte (mm)	50	50
Cranklengte (mm)	165	165

Deze specificaties zijn met de grootste zorgvuldigheid samengesteld. Specificaties, beschikbaarheid, prijzen en kleuren kunnen echter zonder vooraankondiging wijzigen.