



ŠPECIFIKÁCIE

RÁM	
VELKOSTI	S/M, M/L, L/XL
FARBY	Shoreline/Carbon
RÁM	Advanced-grade composite front and rear triangles, 200mm Maestro suspension, flip chip - headset, flip chip - dropout DH, flip chip - Maestro 3, 12x157mm thru-axle, 27.5 or 29-inch rear wheel compatible
VIDLICA	Fox 40 Factory, GRIP2 damper, 203mm, 20x110, custom tuned for Giant
TLMIČ	Fox DHX2 Factory, SLS coil, 225/75, custom tuned for Giant S/M #425, M/L #450, L/XL #475
KOMPONENTY	
RIADIDLÁ	Giant Contact SL TR35, composite, 800x35mm, 20mm rise
GRIPY	Giant Tactal Pro Single
PREDSTAVEC	TruVativ Descendant Direct Mount, 35 S/M:50mm, M/L:50mm, L/XL:50mm
SEDLOVKA	Giant Contact, 30.9mm, 0 offset, 400mm
SEDADLO	Giant Romero
POHON	
RADENIE	SRAM GX Eagle DH, 1x7
PREŠMYKAČ	N/A
PREHADZOVAČKA	SRAM GX Eagle DH
BRZDY	Shimano Saint M-820, hydraulic, Shimano RT-66 rotors, [F]220mm, [R]203mm
BRZDOVÉ PÁKY	Shimano Saint BL-M820
KAZETA	SRAM GX DH, 11-25
REŤAZ	SRAM PC 1110
KLUKY	TruVativ Descendent DH, 34t, 56.5mm chainline, S/M:165mm, M/L:170mm, L/XL:170mm
STREDOVÉ ZLOŽENIE	SRAM DUB, threaded, 83mm

KOLESÁ	
RÁFIKY	Giant AM30, alloy, 28-hole, 30mm inner width
NÁBOJE	[F] alloy, sealed cartridge, 6-bolt, 20x110mm [R] alloy, 72t pawl driver, sealed cartridge, 6-bolt, 12x157mm
ŠPICE	Sapim Laser, straight pull, DBL
PNEUMATIKY	[F] Maxxis Assegai 29x2.5 WT, 3C MaxxGrip, DH, TR [R] Maxxis Minion DHR II 27.5x2.4 WT, 3C, MaxxGrip, DH, TR tubeless
DOPLNKY	tubeless prepared, 2.5" max tire size, 36t max chainring size, MRP SXg chain guide, full downtube protector. *Not compatible with 2023 or earlier RockShox BoXXer Ultimate or BoXXer Select

GEOMETRIA

RÁM	S/M	M/L	L/XL
	LOW MID HIGH	LOW MID HIGH	LOW MID HIGH
Dĺžka sedlovej trubky (mm)	430	450	450
Hĺbka vloženia sedlovky (mm)	155	165	165
Uhol sedlovej trubky	78,4° 78,7° 79,1°	78,4° 78,8° 79,1°	78,5° 78,8° 79,1°
Dĺžka hornej rámovej trubky (mm)	571,2 570,5 569,8	591,3 590,5 589,8	611,3 610,6 609,8
Dĺžka hlavovej trubky (mm)	110	110	110
Uhol hlavovej trubky	61,6° 61,9° 62,3°	61,6° 62,0° 62,3°	61,7° 62,0° 62,3°
Offset vidlice (mm)	52	52	52
Trail (mm)	146,4 143,6 140,8	146,2 143,5 140,8	146 143,3 140,8
Rázvor (mm)	1273 1271,9 1270,6	1293 1291,8 1290,6	1313 1311,9 1310,6
Dĺžka zadnej stavby (mm)	447,9 446,5 445	447,9 446,5 445	447,9 446,5 445
Rozdiel zadnej voči stredovej osi - BB DROP (mm)	13,1 8,1 3	13,3 8,3 3,1	13,5 8,4 3,2
Stack - výška riadenia (mm)	634,6 631,9 629,1	634,9 632,2 629,2	635,3 632,4 629,2
Reach (mm)	440,9 444,7 448,6	461,2 464,9 468,6	481,5 485,1 489,2
Výška rámu od zeme (mm)	733,7 738,2 742,9	735,2 740 744,8	742,9 747,6 752,4
Šírka riaditok (mm)	800	800	800
Dĺžka predstavca (mm)	50	50	50
Dĺžka klúku (mm)	165	165	165
Rozmer kolies	[R] 27.5" / [F] 29"	[R] 27.5" / [F] 29"	[R] 27.5" / [F] 29"

Všetky ceny a špecifikácie sa môžu zmeniť bez predchádzajúceho upozornenia.