



SPECIFIKACIJE

OKVIR	
VELIKOSTI	S/M, M/L, L/XL
BARVE	Shoreline/Carbon
OKVIR	Advanced-grade composite front and rear triangles, 200mm Maestro suspension, flip chip - headset, flip chip - dropout DH, flip chip - Maestro 3, 12x157mm thru-axle, 27.5 or 29-inch rear wheel compatible
VILICE	Fox 40 Factory, GRIP2 damper, 203mm, 20x110, custom tuned for Giant
AMORTIZER	Fox DHX2 Factory, SLS coil, 225/75, custom tuned for Giant S/M #425, M/L #450, L/XL #475
KOMPONENTE	
KRMILO	Giant Contact SL TR35, composite, 800x35mm, 20mm rise
GRIPS	Giant Tactal Pro Single
OPORA KRMILA	TruVativ Descendant Direct Mount, 35 S/M:50mm, M/L:50mm, L/XL:50mm
OPORA SEDEŽA	Giant Contact, 30.9mm, 0 offset, 400mm
SEDEŽ	Giant Romero
POGON	
PRESTAVNE ROČICE	SRAM GX Eagle DH, 1x7
PREDNJI MENJALNIK	N/A
ZADNJI MENJALNIK	SRAM GX Eagle DH
ZAVORE	Shimano Saint M-820, hydraulic, Shimano RT-66 rotors, [F]220mm, [R]203mm
ZAVORNE ROČICE	Shimano Saint BL-M820
VERIŽNIK	SRAM GX DH, 11-25
VERIGA	SRAM PC 1110
GONILKE Z VERIŽNIKI	TruVativ Descendent DH, 34t, 56.5mm chainline, S/M:165mm, M/L:170mm, L/XL:170mm
BOTTOM BRACKET	SRAM DUB, threaded, 83mm

OBROČNIKI	
OBROČI	Giant AM30, alloy, 28-hole, 30mm inner width
PESTA	[F] alloy, sealed cartridge, 6-bolt, 20x110mm [R] alloy, 72t pawl driver, sealed cartridge, 6-bolt, 12x157mm
NAPERE	Sapim Laser, straight pull, DBL
PLAŠČI	[F] Maxxis Assegai 29x2.5 WT, 3C MaxxGrip, DH, TR [R] Maxxis Minion DHR II 27.5x2.4 WT, 3C, MaxxGrip, DH, TR tubeless
DODATKI	tubeless prepared, 2.5" max tire size, 36t max chainring size, MRP SXg chain guide, full downtube protector. *Not compatible with 2023 or earlier RockShox BoXXer Ultimate or BoXXer Select

GEOMETRIJA

OKVIR	S/M	M/L	L/XL
	LOW MID HIGH	LOW MID HIGH	LOW MID HIGH
Dolžina sedežne cevi (mm)	430	450	450
Seat Post Insertion Depth (mm)	155	165	165
Kot sedežne cevi	78,4° 78,7° 79,1°	78,4° 78,8° 79,1°	78,5° 78,8° 79,1°
Top Tube Length (mm)	571,2 570,5 569,8	591,3 590,5 589,8	611,3 610,6 609,8
Višina glave okvirja (mm)	110	110	110
Krmilni kot	61,6° 61,9° 62,3°	61,6° 62,0° 62,3°	61,7° 62,0° 62,3°
Zamik vpetja osi (mm)	52	52	52
Trail (mm)	146,4 143,6 140,8	146,2 143,5 140,8	146 143,3 140,3
Medosna razdalja (mm)	1273 1271,9 1270,6	1293 1291,8 1290,6	1313 1311,9 1310,6
Dolžina cevi ob verigi (mm)	447,9 446,5 445	447,9 446,5 445	447,9 446,5 445
Bottom Bracket Drop (mm)	13,1 8,1 3	13,3 8,3 3,1	13,5 8,4 3,2
Oddaljenost zgornje cevi od gonilne osi (mm)	634,6 631,9 629,1	634,9 632,2 629,2	635,3 632,4 629,2
Doseg (mm)	440,9 444,7 448,6	461,2 464,9 468,6	481,5 485,1 488,6
Višina zgornje cevi (mm)	733,7 738,2 742,9	735,2 740 744,8	742,9 747,6 752,3
Širina krmila (mm)	800	800	800
Dolžina opore krmila (mm)	50	50	50
Dolžina gonilke (mm)	165	165	165
Velikost obročnikov	[R] 27.5" / [F] 29"	[R] 27.5" / [F] 29"	[R] 27.5" / [F] 29"

Vse navedene specifikacije se lahko spremenijo brez obvestila.