

GLORY ADVANCED

GIANT



SPECIFIKACIJE

OKVIR	
VELIKOSTI	S/M, M/L, L/XL
BARVE	Moon Dust
OKVIR	Advanced-grade composite front and rear triangles, 200mm Maestro suspension, flip chip - headset, flip chip - dropout DH, flip chip - Maestro 3, 12x157mm thru-axle, 27.5 or 29-inch rear wheel compatible
VILICE	Fox 40 Factory, GRIP X2 damper, 203mm, 20x110
AMORTIZER	Fox DHX2 Factory, SLS coil, 225/75 S/M:425#, M/L:450#, L/XL:475#
KOMPONENTE	
KRMILO	Giant Contact SL TR35, 800x35mm, 20mm rise
GRIPS	Giant Tactal Pro Single
OPORA KRMILA	TruVativ Descendant Direct Mount 35 S/M:50mm, M/L:50mm, L/XL:50mm
OPORA SEDEŽA	Giant Contact, 30.9mm, 0 offset, 400mm
SEDEŽ	Giant Romero
PEDALA	platform [GC,GT]
POGON	
PRESTAVNE ROČICE	TRP EVO 7 DH, 1x7
PREDNJI MENJALNIK	N/A
ZADNJI MENJALNIK	TRP EVO 7 DH
ZAVORE	TRP EVO Pro, hydraulic, TRP rotors [F]220mm, [R]203mm
ZAVORNE ROČICE	TRP EVO Pro
VERIŽNIK	TRP EVO 7 DH, 11-24
VERIGA	KMC X-11
GONILKE Z VERIŽNIKI	TRP EVO 7 DH, 34t, 56.5mm chainline S/M:165mm, M/L:165mm, L/XL:165mm
BOTTOM BRACKET	TRP, threaded, 83mm

OBROČNIKI	
OBROČI	Giant TRA 2 rims, 6061 alloy, hookless, 30mm inner width, 40mm outer width, 21mm height, Wide Guard Technology
PESTA	[F] Giant MTB alloy, 6-bolt [R] Giant MTB alloy, 30t 3-pawl driver, 6-bolt
NAPERE	Stainless steel
PLAŠČI	[F] Maxxis Assegai 29x2.5 WT, 3C MaxxGrip, DH, TR [R] Maxxis Minion DHR II 27.5x2.4 WT, 3C, MaxxGrip, DH, TR tubeless
DODATKI	tubeless prepared, 2.5" max tire size, 36t max chainring size, MRP SXg chain guide, full down tube protector

GEOMETRIJA

OKVIR	L/XL			S/M			M/L		
	LOW	MID	HIGH	LOW	MID	HIGH	LOW	MID	HIGH
Dolžina sedežne cevi (mm)	450			430			450		
Seat Post Insertion Depth (mm)	165			155			165		
Kot sedežne cevi	78,5° 78,8° 79,1°			78,4° 78,7° 79,1°			78,4° 78,8° 79,1°		
Top Tube Length (mm)	611 611 610			571 571 570			591 591 590		
Višina glave okvirja (mm)	110			110			110		
Krmlilni kot	61,7° 62,0° 62,3°			61,6° 61,9° 62,3°			61,6° 62,0° 62,3°		
Zamik vpetja osi (mm)	52			52			52		
Trail (mm)	146 143,3 140,8			146,4 143,6 140,8			146,2 143,5 140,8		
Medosna razdalja (mm)	1313 1312 1311			1273 1272 1271			1293 1292 1291		
Dolžina cevi ob verigi (mm)	448 447 445			448 447 445			448 447 445		
Bottom Bracket Drop (mm)	14 8 3			13 8 3			13 8 3		
Oddaljenost zgornje cevi od gonilne osi (mm)	635 632 629			635 632 629			635 632 629		
Doseg (mm)	482 485 489			441 445 449			461 465 469		
Višina zgornje cevi (mm)	743 748 752			734 738 743			735 740 745		
Širina krmila (mm)	800			800			800		
Dolžina opore krmila (mm)	50			50			50		
Dolžina gonilke (mm)	165			165			165		

Vse navedene specifikacije se lahko spremenijo brez obvestila.