GLORY ADVANCED



SPECS

RAM	
STORLEKAR	S/M, M/L, L/XL
FÄRGER	Moon Dust
RAM	Advanced-grade composite front and rear triangles, 200mm Maestro suspension, flip chip - headset, flip chip - dropout DH, flip chip - Maestro 3, 12x157mm thru-axle, 27.5 or 29-inch rear wheel compatible
GAFFEL	Fox 40 Factory, GRIP X2 damper, 203mm, 20x110
BAKDÄMPARE	Fox DHX2 Factory, SLS coil, 225/75 S/M:425#, M/L:450#, L/XL:475#
KOMPONENTER	
STYRE	Giant Contact SL TR35, 800x35mm, 20mm rise
GREPPAR	Giant Tactal Pro Single
STAM	TruVativ Descendant Direct Mount 35 S/M:50mm, M/L:50mm, L/XL:50mm
SADELSTOLPE	Giant Contact, 30.9mm, 0 offset, 400mm
SADEL	Giant Romero
PEDALER	platform [GC,GT]
DRIVLINA	
VÄXLAR	TRP EVO 7 DH, 1x7
FRAMVÄXEL	N/A
BAKVÄXEL	TRP EVO 7 DH
BROMSAR	TRP EVO Pro, hydraulic, TRP rotors [F]220mm, [R]203mm
BROMSSPAKAR	TRP EVO Pro
KASSETT	TRP EVO 7 DH, 11-24
KEDJA	KMC X-11
VEVPARTI	TRP EVO 7 DH, 34t, 56.5mm chainline S/M:165mm, M/L:165mm, L/XL:165mm
BROMSREGLAGE	TRP, threaded, 83mm

HJUL	
FÄLGAR	Giant TRA 2 rims, 6061 alloy, hookless, 30mm inner width, 40mm outer width, 21mm height, Wide Guard Technology
NAV	[F] Giant MTB alloy, 6-bolt [R] Giant MTB alloy, 30t 3-pawl driver, 6-bolt
EKRAR	Stainless steel
DÄCK	[F] Maxxis Assegai 29x2.5 WT, 3C MaxxGrip, DH, TR [R] Maxxis Minion DHR II 27.5x2.4 WT, 3C, MaxxGrip, DH, TR tubeless
EXTRAFUNKTIONER	tubeless prepared, 2.5" max tire size, 36t max chainring size, MRP SXg chain guide, full down tube protector

Price: 94 000,00 kr

GEOMETRY

RAM	L/XL	M/L
	LOW | MID | HIGH	LOW | MID | HIGH
Längd sadelrör (mm)	450	450
Seat Post Insertion Depth (mm)	165	165
Vinkel sadelrör	78,5° | 78,8° | 79,1°	78,4° | 78,8° | 79,1°
Topprörets längd (mm)	611 | 611 | 610	591 | 591 | 590
Styrhuvud Längd (mm)	110	110
Vinkel styrhuvud	61,7° | 62,0° | 62,3°	61,6° | 62,0° | 62,3°
Gaffelvinkel (mm)	52	52
Spår (mm)	146 | 143,3 | 140,8	146,2 | 143,5 | 140,8
Hjulbas (mm)	1313 | 1312 | 1311	1293 | 1292 | 1291
Kedjestagslängd (mm)	448 | 447 | 445	448 | 447 | 445
Nedre fäste Drop (mm)	14 | 8 | 3	13 | 8 | 3
Stack (mm)	635 | 632 | 629	635 | 632 | 629
Reach (mm)	482 | 485 | 489	461 | 465 | 469
Stå över höjden (mm)	743 | 748 | 752	735 | 740 | 745
Styrets bredd (mm)	800	800
Stamlängd (mm)	50	50
Vevlängd (mm)	165	165

All specifications listed are subject to change without notice.