

GRAVIER



SPECIFIKACIJE

OKVIR	
VELIKOSTI	XS,S,M,L
BARVE	Satin Cold Iron(サテンコールドアイアン),Satin Kelp Forest(サテンケルプフォレスト),Matt Titanium(マットチタニウム)
OKVIR	ALUXX-Grade Aluminum, OLD135mm ※リアエンド型番：RE5XE
VILICE	Steel
KOMPONENTE	
KRMILO	Aluminum 25.4 XS:560mm, S:580mm, M:580mm, L:580mm
GRIPS	Comfort Grip
OPORA KRMILA	Aluminum 25.4 XS:90mm, S:90mm, M:105mm, L:105mm
OPORA SEDEŽA	Aluminum 27.2 XS:300mm, S:300mm, M:300mm, L:375mm
SEDEŽ	Giant Connect Comfort w/Uniclip System
PEDALA	Plastic Cage
HEADSET	Feimin Semi-Cartridge
POGON	
PRESTAVNE ROČICE	Shimano EF500 3x8
PREDNJI MENJALNIK	Shimano TY601
ZADNJI MENJALNIK	Shimano Altus
ZAVORE	Tektro TK837AL
ZAVORNE ROČICE	Shimano EF500
VERIŽNIK	Shimano HG31 11x32
VERIGA	KMC Z8.3
GONILKE Z VERIŽNIKI	Prowheel TY-CQ99 28/38/48T/CG XS:165mm,S:170mm,M:170mm,L:175mm
BOTTOM BRACKET	VP BC73 124.5-68mm

OBROČNIKI	
OBROČI	Aluminum WheelSet F:28H R:28H
PESTA	Aluminum WheelSet F:28H R:28H
NAPERE	Stainless 14G
PLAŠČI	KENDA K-1082 27.5x1.75
DODATKI	ベル、リフレクター

GEOMETRIJA

OKVIR	XXS	XS	S	M	L
Dolžina sedežne cevi (mm)	365	430	465	500	555
Kot sedežne cevi	75,0°	75,0°	74,0°	73,0°	73,0°
Top Tube Length (mm)	505	525	545	565	590
Višina glave okvirja (mm)	105	125	145	170	200
Krmilni kot	71,0°	71,0°	72,0°	72,5°	72,5°
Zamik vpetja osi (mm)	50	50	50	50	50
Trail (mm)	66	66	59	56	56
Medosna razdalja (mm)	1008	1020	1021	1025	1053
Dolžina cevi ob verigi (mm)	430	430	430	430	430
Bottom Bracket Drop (mm)	70	70	70	70	65
Oddaljenost zgornje cevi od gonilne osi (mm)	531	550	573	599	622
Doseg (mm)	363	378	381	382	400
Širina krmila (mm)	560	560	580	580	580
Dolžina opore krmila (mm)	60	90	90	105	105
Dolžina gonilke (mm)	160	165	170	170	175
Velikost obročnikov	27.5inch	27.5inch	27.5inch	27.5inch	27.5inch

Vse navedene specifikacije se lahko spremenijo brez obvestila.