

KIT CADRE REIGN ADVANCED



TECHNIQUES

CADRE	
TAILLES	S, M, L, XL
COLORIS	Glacier Storm
CADRE	Advanced-grade composite front and rear triangles, 160mm Maestro suspension, flip chip, 12x148mm thru-axle, 27.5 or 29-inch rear wheel compatible, flip chip - Maestro 3, integrated down tube storage
AMORTISSEUR	Fox Float DHX2 Factory 2 position adjust, Trunnion mount, 205x62,5, custom tuned for Giant, recommended sag 30%

ROUES	
EXTRAS	2.5" max tire size, 36t max chainring size, MRP AMG CS chain guide, 3M tailgate protector
LIMITES	
TAILLE MAXIMALE DU PLATEAU	36T

Prix Public Conseillé: 4 500,00 €

GÉOMÉTRIE

CADRE	S			M			L			XL		
	LOW	MID	HIGH	LOW	MID	HIGH	LOW	MID	HIGH	LOW	MID	HIGH
Longueur de tube de selle (mm)	400			425			450			475		
Seat Post Insertion Depth (mm)	262			287			312			337		
Angle de tube de selle	78,3°	78,7°	79,0°	78,3°	78,7°	79,0°	77,3°	77,7°	78,0°	77,3°	77,7°	
Longueur du tube supérieur (mm)	556	555	555	587	586	585	620	620	619	652	652	
Longueur du tube de direction (mm)	100			105			115			120		
Angle du tube de direction	63,5°	63,9°	64,2°	63,5°	63,9°	64,2°	63,5°	63,9°	64,2°	63,5°	63,9°	64,2°
Déport de fourche (mm)	44			44			44			44		
Trail (mm)	140	138	135	140	138	135	140	138	135	140	138	135
Empattement (mm)	1214	1213	1212	1246	1245	1244	1271	1270	1269	1304	1303	1302
Longueur des bases (mm)	445	443	442	445	443	442	445	443	442	445	443	442
Drop du boîtier de pédalier (mm)	35	30	25	35	30	25	35	30	25	35	30	25
Stack (mm)	627	624	622	632	629	626	641	638	635	645	642	640
Reach (mm)	426	430	434	456	460	464	476	480	484	506	510	514
Hauteur en statique (mm)	720	724	729	735	739	744	751	756	760	746	751	756
Largeur de cintre (mm)	800			800			800			800		
Longueur de potence (mm)	40			40			40			40		
Longueur des manivelles (mm)	165			170			170			170		
Diamètre des roues	29"			29"			29"			29"		

Produits conformes aux exigences de sécurité (décret n° 2016-364 du 29 mars 2016).
GIANT France se réserve le droit de modifier les spécifications sans préavis.