

KIT CADRE VÉLO ROUTE PROPEL ADVANCED SL TEAM JAYCO ALULA

GIANT



TECHNIQUES

CADRE	
TAILLES	XS, S, M, M/L, L, XL
COLORIS	Nitro Purple
CADRE	Advanced SL-grade Composite, 12x142mm thru-axle, integrated seatpost, disc
FOURCHE	Advanced SL-grade composite, full-composite OverDrive Aero steerer, 12x100mm thru-axle, disc
COMPOSANTS	
TIGE DE SELLE	Advanced SL-grade composite, integrated design, -5/+15mm offset

ROUES

EXTRAS water bottle cages, 32mm max tire size

Prix Public Conseillé: 3 950,00 €

GÉOMÉTRIE

CADRE	XS	S	M	M/L	L	XL
Longueur de tube de selle (mm)	680	710	740	770	800	830
Angle de tube de selle	74,5°	74,0°	73,5°	73,0°	73,0°	72,5°
Longueur du tube supérieur (mm)	520	535	550	565	580	600
Longueur du tube de direction (mm)	115	127	145	165	185	200
Angle du tube de direction	71,5°	72,5°	73,0°	73,0°	73,0°	73,0°
Déport de fourche (mm)	45	45	45	45	45	45
Trail (mm)	67,8	61,4	58,3	58,3	58,3	58,3
Empattement (mm)	971	973	980	990	1006	1020
Longueur des bases (mm)	405	405	405	405	405	405
Drop du boîtier de pédalier (mm)	72	72	69,5	69,5	67	67
Stack (mm)	515	530	546	565	582	596
Reach (mm)	377	383	388	392	402	412
Hauteur en statique (mm)	746	764	787	808	832	847
Largeur de cintre (mm)	380	380	400	400	420	420
Longueur de potence (mm)	80	90	100	110	110	120
Longueur des manivelles (mm)	165	165	170	170	172,5	172,5
Diamètre des roues	700C	700C	700C	700C	700C	700C

Produits conformes aux exigences de sécurité (décret n° 2016-364 du 29 mars 2016).
GIANT France se réserve le droit de modifier les spécifications sans préavis.