



스펙

프레임	
사이즈	S, M, L, XL
색상	T/K
프레임	ALUXX-grade aluminum, 130mm FlexPoint suspension, 12x148mm thru-axle, UDH interface, external storage solution
포크	Giant STL 34 dual air, 140mm, 15x110, thru-axle
서스펜션	GU: Fox Rhythm, rebound, 210x52.5 Other GSCs: Crest FloTrac Elite TR, 2-position lockout, 210x52.5
부품	
핸들바	Giant Contact TR35, 35mm XS:20mm rise/760mm, S:20mm rise/760mm, M:35mm rise/760mm, L:35mm rise 800mm, XL:35mm rise 800mm
GRIPS	Giant Tactal, lock on
스템	Giant Contact SL 35 XS: 40mm, S:40mm, M:40mm, L:40mm, XL:40mm
시프스트	Giant Contact Switch AT dropper, remote XS: 110-140mm travel / 30.9 x 395mm S: 110-140mm travel / 30.9 x 395mm M: 140-170mm travel / 30.9 x 470mm L: 170-200mm travel / 30.9 x 530mm XL: 170-200mm travel / 30.9 x 530mm
안장	Giant Contact Ergo Trail
구동계	
변속기	Shimano CUES SL-6000, 1x10
앞 변속기	N/A
뒷 변속기	Shimano CUES RD-U6000, Shadow +
브레이크	Tektro HD-M5141, hydraulic, TR-54, 6-bolt rotors [F]180mm, [R]180mm
브레이크 레버	Tektro HD-M5141
스프라켓	Shimano CUES, CS-LG300, 11x48
체인	KMC X-11
크랭크 셋	Shimano CUES FC-U6000, 30t XS: 165mm, S:165mm, M:165mm, L:165mm, XL:165mm
BB	Shimano, threaded

바퀴	
립	Giant AM30 alloy rim
허브	[F] Giant MTB alloy, 6-bolt [R] Giant MTB alloy, 6-bolt, HG driver body
스포크	stainless, 28, J-bend
타이어	[F] Maxxis Dissector 29x2.4, Dual, EXO, TR [R] Maxxis Dissector 29x2.4, Dual, EXO, TR, tubeless
추가 기능	tubeless prepared, max tire size 2.5", max chainring size 32t

가격: ₩2,690,000

지오메트리

프레임	XS	S	M
시트 튜브 길이 (mm)	380	400	425
Seat Post Insertion Depth (mm)	250	270	290
시트 튜브 각도	77.0°	76.5°	76.5°
탑튜브 길이 (mm)	547	567	600
헤드 튜브 길이 (mm)	95	100	110
헤드튜브 각도	65.0°	65.0°	65.0°
포크 레이크 (mm)	44	44	44
트레일 (mm)	129	129	129
휠베이스 (mm)	1158	1176	1210
체인스테이 길이 (mm)	440	442	442
BB (mm)	25	40	40
스택 (mm)	613	615	624
범위 (mm)	405	420	450
스탠드 오버 (mm)	758	754	748
핸들바 폭 (mm)	760	760	760
스템 길이 (mm)	40	40	40
크랭크 길이 (mm)	165	165	165
휠사이즈	29" [F] 27.5" [R]	29"	29"

상기 스펙은 글로벌 스펙이며, 실제 구성과 차이가 있을 수 있습니다. 정확한 스펙은 매장을 방문하여 확인해주시기 바랍니다.