



스펙

프레임	
사이즈	S, M, L, XL
색상	Luminous Lagoon/Chrome
프레임	Advanced-grade composite front and rear triangles, 160mm Maestro suspension, flip chip, 12x148mm thru-axle, 27.5 or 29-inch rear wheel compatible, flip chip - Maestro 3, integrated down tube storage
포크	RockShox Zeb Ultimate, Charger 3.2 RC2 damper, 170mm, 15x110, Maxle Stealth, Debonair
서스펜션	RockShox Vivid Ultimate, RCT2, adjustable hydraulic bottom out, trunnion mount, 205/65 S:425#, M:425#, L:450#, XL: 475#
부품	
핸들바	Giant Contact TR35, 800x35mm, 35mm rise
GRIPS	Giant Tactal Pro Single
스텝	Giant Contact SL 35 S:40mm, M:40mm, L:40mm, XL:40mm
시프스트	Contact Switch AT dropper, remote S: 110-140mm travel / 30.9 x 395mm M: 140-170mm travel / 30.9 x 470mm L: 170-200mm travel / 30.9 x 530mm XL: 170-200mm travel / 30.9 x 530mm
안장	Giant Romero SL
구동계	
변속기	SRAM AXS Pod, 1x12
뒷 변속기	SRAM GX AXS Transmission
브레이크	TRP EVO Pro, hydraulic, TRP rotors [F]220mm, [R]203mm
브레이크 레버	TRP EVO Pro
스프라켓	SRAM GX Eagle Transmission, 10x52
체인	SRAM GX Eagle Transmission
크랭크 셋	SRAM GX Eagle Transmission, DUB, 32t, 55mm chainline S:165mm, M:170mm, L:170mm, XL:170mm
BB	SRAM DUB, press fit

바퀴	
립	Giant TRA WheelSystem, 6069 alloy, hookless, 30mm inner width, 40mm outer width, 21mm height, Wide Guard Technology
허브	[F] Giant MTB alloy, 6-bolt [R] Giant MTB alloy, 72 POE (Points of Engagement), 6-bolt, XD driver body
스포크	Sapim, 28, straight pull, DBL Technology
타이어	[F] Maxxis Assegai 29x2.5 WT, MaxxTerra, EXO+, TR [R] Maxxis Minion DHR II 27.5x2.4 WT, MaxxTerra, DD, TR tubeless
추가 기능	tubeless prepared, 2.5" max tire size, 36t max chainring size, MRP AMG CS chain guide, 3M tailgate protector

가격: ₩8,290,000

지오메트리

프레임	S	M
	LOW MID HIGH	LOW MID HIGH
시트 튜브 길이 (mm)	400	425
Seat Post Insertion Depth (mm)	262	287
시트 튜브 각도	77.5° 77.8° 78.2°	77.5° 77.8° 78.2°
탑튜브 길이 (mm)	558 557 556	589 588 587
헤드 튜브 길이 (mm)	100	105
헤드튜브 각도	62.7° 63.0° 63.4°	62.7° 63.0° 63.4°
포크 레이아웃 (mm)	44	44
트레일 (mm)	147 144 141	147 144 141
휠베이스 (mm)	1214 1213 1212	1246 1245 1244
체인스테이 길이 (mm)	445 443 442	445 443 442
BB (mm)	29 24 19	29 24 19
스택 (mm)	633 630 627	638 635 632
범위 (mm)	418 421 426	448 452 456
스탠드 오버 (mm)	714 718 723	733 738 742
핸들바 폭 (mm)	800	800
스텝 길이 (mm)	40	40
크랭크 길이 (mm)	165	170
휠사이즈	29" [F] 27.5" [R]	29" [F] 27.5" [R]

상기 스펙은 글로벌 스펙이며, 실제 구성과 차이가 있을 수 있습니다. 정확한 스펙은 매장을 방문하여 확인해주시기 바랍니다.