

NEWTOUR E+ 0 LST



SPECIFICATIES

HYBRID CYCLING TECHNOLOGY	
MOTOR	Giant SyncDrive Core2 55Nm, PedalPlus 6-Sensor technology
BEDIENINGSUNIT	Giant RideControl Dash 2, Smart Assist automatic mode, 5 support levels
DISPLAY	Giant RideControl Dash 2, full color LCD display
ACCU	Persoonlijke accukeuze: 500 Wh, 625 Wh of 800 Wh accu (adviesprijs op basis van 500 Wh)
LADER	Giant EnergyPak 4A smart charger
FRAME	
MATEN	S, M, L, XL
KLEUREN	Charcoal
FRAME	ALUXX aluminium Battery Integrated, low step through design
VOORVORK	SR Suntour Mobie 32 63mm travel 15x100 thru-axle
ONDERDELEN	
STUUR	Aluminium, 30° back sweep, 31.8x660 mm
HANDVATTEN	Comfort Ergo Microtech Plus
STUURPEN	Aluminum angle adjustable stem
ZADEL	Selle Royal Essenza Plus
PEDALEN	Anti-slip Platform
AFMONTAGE	
SHIFTERS	Enviolo Pure w/o Display
ACHTERDERAILLEUR	Enviolo City V3 Manual
REMMEN	Tektro HD-M281, hydraulic disc, 180mm [F] 160mm [R]
REMHENDELS	Tektro HD-M281
CASSETTE	Gates CDC stainless steel 22T rear sprocket
AANDRIJVING	Gates CDC Carbon Drive 122T CenterTrack belt
CRANKSET	Gates CDC CenterTrack 46T front sprocket, Forged aluminum crank arms

WIELSET	
VELGEN	Giant Double Wall Aluminum 622x21
NAVEN	Giant 15x100 mm [F] Enviolo City V3 [R]
SPAKEN	Stainless 14G(2.0mm) [F] Stainless 13-14G(2.3-2.0mm) butted [R]
BANDEN	Schwalbe Road Cruiser Plus, 622x50 Wire Bead w/ reflective stripe
EXTRA'S	KSA18 direct mount kickstand
LIMITS	
COMPATIBILITY	Aegis Tire Checker
ACCESSOIRES	
VERLICHTING	Giant Recon HL50, 50 lux [F] Carrier integrated tail light [R]
SLOT	ABUS 4750X R (w/o chip) LH OEM
DRAGER	MIK HD rack. System bag & basket compatible
SPATBORD/ KETTINGKAST	Aluminium Fender w/ Z-Reflector, Pistol Shape

Adviesprijs: € 3.299,00

GEOMETRIE

FRAME	S	M	L	XL
Zitbuis Lengte (mm)	450	500	550	600
Zitbuis Hoek	757,0°	742,0°	728,0°	712,0°
Frame Lengte (horizontaal) (mm)	590	605	620	635
Balhoofdbuis Lengte (mm)	170	170	170	170
Balhoofdbuis Hoek	69,0°	69,0°	69,0°	69,0°
Vork Sprong (mm)	44	44	44	44
Naloop (mm)	957	957	957	957
Wielbasis (mm)	1155	1155	1155	1155
Liggende achtervork lengte (mm)	4823	4823	4823	4823
Bottom Bracket Drop (mm)	75	75	75	75
Stack (mm)	672	672	672	672
Reach (mm)	405	405	405	405
Stuur breedte (mm)	660	660	660	660
Stuurpen Lengte (mm)	70	70	90	110
Cranklengte (mm)	170	170	170	170
Wielmaat	622X50	622X50	622X50	622X50

Deze specificaties zijn met de grootste zorgvuldigheid samengesteld. Specificaties, beschikbaarheid, prijzen en kleuren kunnen echter zonder voor aankondiging wijzigen.