

NEWTOUR E+ 1 DD



SPECIFIKACIJE

HIBRIDNA GONILNA TEHNOLOGIJA	
MOTOR	Giant SyncDrive Core2 55Nm, PedalPlus 6-Sensor technology
TIPALO	Giant RideControl Dash 2, Smart Assist automatic mode, 5 support levels
PRIKAZOVALNIK	Giant RideControl Dash 2, full color LCD display
BATERIJA	Giant EnergyPak 625Wh
CHARGER	Giant EnergyPak 4A smart charger
OKVIR	
VELIKOSTI	M, L, XL
OKVIR	ALUXX aluminium Battery Integrated, low step through design
VILICE	SR Suntour Mobie 32 63mm travel
KOMPONENTE	
KRMILO	Aluminium, 30° back sweep, 31.8x660 mm
GRIPS	Comfort Ergo Microtech Plus
OPORA KRMILA	Aluminum angle adjustable stem
OPORA SEDEŽA	Suspension 30.9x300mm
SEDEŽ	Selle Royal Essenza Plus
PEDALA	VP-Low Cost platform pedal
POGON	
PRESTAVNE ROČICE	Shimano Nexus 8 RevoShift
ZAVORE	Tektro HD-M281, hydraulic disc, 180mm [F] 160mm [R]
ZAVORNE ROČICE	Tektro HD-M281
VERIŽNIK	Gates CDC stainless steel 22T rear sprocket
VERIGA	Gates CDC Carbon Drive 122T CenterTrack belt
GONILKE Z VERIŽNIKI	Gates CDC CenterTrack 46T front sprocket, Forged alumium crank arms

OBROČNIKI	
OBROČI	Giant Double Wall Aluminum 622x21
PESTA	Shimano HB-QC300 [F] Shimano Nexus 8 disc brake [R]
NAPERE	Stainless 14G(2.0mm) [F] Stainless 13-14G(2.3-2.0mm) butted [R]
PLAŠČI	Schwalbe Road Cruiser Plus, 622x50 Wire Bead w/ reflective stripe
DODATKI	KSA18 direct mount kickstand
LIMITS	
COMPATIBILITY	Aegis Tire Checker
DODATNA OPREMA	
SVETILA	Giant Recon HL50, 50 lux [F] Carrier integrated tail light [R]
KLJUČAVNICA	ABUS 4750X NR (w/o chip) LH OEM
PRTLJAŽNIK	MIK HD rack. System bag & basket compatible
BLATNIKI/ŠČITNIK VERIGE	Aluminium Fender w/ Z-Reflector, Pistol Shape

GEOMETRIJA

OKVIR	S	M	L	XL
Dolžina sedežne cevi (mm)	450	500	550	600
Seat Post Insertion Depth (mm)	270	290	320	390
Kot sedežne cevi	757,0°	742,0°	728,0°	712,0°
Top Tube Length (mm)	590	605	620	635
Višina glave okvirja (mm)	170	170	170	170
Krmilni kot	69,0°	69,0°	69,0°	69,0°
Zamik vpetja osi (mm)	44	44	44	44
Trail (mm)	957	957	957	957
Medosna razdalja (mm)	1155	1155	1155	1155
Dolžina cevi ob verigi (mm)	4823	4823	4823	4823
Bottom Bracket Drop (mm)	75	75	75	75
Oddaljenost zgornje cevi od gonilne osi (mm)	672	672	672	672
Doseg (mm)	405	405	405	405
Širina krmila (mm)	660	660	660	660
Dolžina opore krmila (mm)	70	70	90	110
Dolžina gonilke (mm)	170	170	170	170
Velikost obročnikov	622X50	622x50	622X50	622X50

Vse navedene specifikacije se lahko spremenijo brez obvestila.