

NEWTOUR E+ 1 LST

GIANT



SPECS

HYBRID CYKELTEKNIK	
MOTOR	Giant SyncDrive Core2 55Nm, PedalPlus 6-Sensor technology
KONTROLLER	Giant RideControl Dash 2, Smart Assist automatic mode, 5 support levels
VISA	Giant RideControl Dash 2, full color LCD display
BATTERI	Personal battery choice 500 Wh, 625 Wh or 800 Wh (suggested retail price based on 500 Wh)
LADDARE	Giant EnergyPak 4A smart charger
RAM	
STORLEKAR	S, M, L, XL
FÄRGER	Eclipse, Desert Sage
RAM	ALUX aluminium Battery Integrated, low step through design
GAFFEL	SR Sountour Mobie 32 63mm travel
KOMPONENTER	
STYRE	Aluminium, 30° back sweep, 31.8x660 mm
GREPPAR	Comfort Ergo Microtech Plus
STAM	Aluminium angle adjustable stem
SADELSTOLPE	Suspension 30.9x300mm
SADEL	Selle Royal Essenza Plus
PEDALER	Anti-slip Platform
DRIVLINA	
VÄXLAR	Shimano Nexus 8 RevoShift
BROMSAR	Tektro HD-M281, hydraulic disc, 180mm [F] 160mm [R]
BROMSSPAKAR	Tektro HD-M281
KASSETT	Gates CDC stainless steel 22T rear sprocket
KEDJA	Gates CDC Carbon Drive 122T CenterTrack belt
VEVPARTI	Gates CDC CenterTrack 46T front sprocket, Forged alumium crank arms

HJUL	
FÄLGAR	Giant Double Wall Aluminum 622x21
NAV	Shimano HB-QC300 [F] Shimano Nexus 8 disc brake [R]
EKRAR	Stainless 14G(2.0mm) [F] Stainless 13-14G(2.3-2.0mm) butted [R]
DÄCK	Schwalbe Road Cruiser Plus, 622x50 Wire Bead w/ reflective stripe
EXTRAFUNKTIONER	KSA18 direct mount kickstand
GRÄNSER	
COMPATIBILITY	Aegis Tire Checker
TILLBEHÖR	
BELYSNING	Giant Recon HL50, 50 lux [F] Carrier integrated tail light [R]
LÅSA	ABUS 4750X R (w/o chip) LH OEM
BÄRARE	MIK HD rack. System bag & basket compatible
STÄNKSKÄRM/KEDJESKYDD	Aluminium Fender w/ Z-Reflector, Pistol Shape

Price: 35 990,00 kr

GEOMETRY

RAM	S	M	L	XL
Längd sadelrör (mm)	450	500	550	600
Vinkel sadelrör	75,7°	74,2°	72,8°	71,2°
Topprörets längd (mm)	590	605	620	635
Styrhuvud Längd (mm)	170	170	170	170
Vinkel styrhuvud	69,0°	69,0°	69,0°	69,0°
Gaffelvinkel (mm)	44	44	44	44
Spår (mm)	95,7	95,7	95,7	95,7
Hjulbas (mm)	1155	1155	1155	1155
Kedjestagslängd (mm)	482,3	482,3	482,3	482,3
Nedre fäste Drop (mm)	75	75	75	75
Stack (mm)	672	672	672	672
Reach (mm)	405	405	405	405
Styrets bredd (mm)	660	660	660	660
Stamlängd (mm)	70	70	90	110
Vevlängd (mm)	170	170	170	170
Hjulstorlek	622X50	622x50	622X50	622X50

All specifications listed are subject to change without notice.