

NEWTOUR E+ 3 LST

GIANT



SPECS

HYBRID CYCLING TECHNOLOGY

MOTOR	Giant SyncDrive Core2 55Nm, PedalPlus 6-Sensor technology
CONTROLLER	Giant RideControl Dash 2, Smart Assist automatic mode, 5 support levels
DISPLAY	Giant RideControl Dash 2, full colour LCD display
BATTERY	Giant EnergyPak 500Wh
CHARGER	Giant EnergyPak 4A smart charger
MAXIMUM ASSISTED SPEED	Pedal-assist limited to 25 km/h in accordance with Australian regulations (EN15194); no motor support above this speed

FRAME

SIZES	S, M, L, XL
COLOURS	Kelp Forest
FRAME	ALUXX-grade aluminium, Integrated battery design, KSA18 Kickstand
FORK	SR Suntour Mobie A32 Coil 29" 5TA 63mm travel, 9x100mm Q/R
SHOCK	N/A

COMPONENTS

HANDLEBAR	Aluminium, 30° back sweep, 31.8mm
GRIPS	Giant Comfort Ergo Microtech Plus
STEM	Aluminium angle adjustable stem, S:90mm, M:90mm, L:110mm, XL:110mm
SEATPOST	Suspension, 30.9mm
SADDLE	Selle Royal Essenza Plus
PEDALS	Platform

DRIVETRAIN

SHIFTERS	Shimano, SL-M315, 1x8
FRONT DERAILLEUR	N/A
REAR DERAILLEUR	Shimano Acera, 8-speed
BRAKES	Tektro HD-M281, hydraulic disc, 180mm [F] 160mm [R]
BRAKE LEVERS	Tektro HD-M281, hydraulic disc
CASSETTE	Shimano HG400, 8-speed, 11-40T
CHAIN	KMC E8 Sport
CRANKSET	Forged Alloy, 38T
BOTTOM BRACKET	N/A

WHEELS

RIMS	Giant GX03, Aluminium
HUBS	Shimano HB-QC300, disc, 32H [F] Shimano FH-QC400-HM, Disc 32H [R]
SPOKES	Stainless steel [F] Stainless steel 13-14G butted [R]
TYRES	Schwalbe Road Cruiser Plus, 29"x50C, Wire Bead w/ reflective stripe
EXTRAS	KSA18 direct mount kickstand

LIMITS

COMPATIBILITY	Aegis Tire Checker
----------------------	--------------------

ACCESSORIES

LIGHTING	Giant Recon HL50, 50 lux [F] Carrier integrated tail light [R]
LOCK	ABUS Xplus battery lock, ABUS Xplus battery lock (does not include Abus ringlock)
CARRIER	MIK rack. System bag & basket compatible
FENDER/CHAINGUARD	Aluminium

Price: \$4,799.00

GEOMETRY

FRAME	S	M	L	XL
Seat Tube Length (mm)	450	500	550	600
Seat Tube Angle	75.7°	74.2°	72.8°	71.2°
Top Tube Length (mm)	590	605	620	635
Head Tube Length (mm)	170	170	170	170
Head Tube Angle	69.0°	69.0°	69.0°	69.0°
Fork Rake (mm)	44	44	44	44
Trail (mm)	95.7	95.7	95.7	95.7
Wheelbase (mm)	1155	1155	1155	1155
Chain Stay Length (mm)	482.3	482.3	482.3	482.3
Bottom Bracket Drop (mm)	75	75	75	75
Stack (mm)	672	672	672	672
Reach (mm)	405	405	405	405
Stem Length (mm)	70	70	90	110
Crank Length (mm)	170	170	170	170
Wheel Size	622x50	622x50	622x50	622x50

Please note that our specifications may be impacted by running substitution changes, we highly recommend confirming the specifications of our products with your local retailer at the time of sale if purchasing in-store. *Recommended Retail Prices are subject to change without notice and may vary from store to store depending on freight and assembly costs.