

리볼트 어드밴스 PRO 0



스펙

프레임	
사이즈	XS, S, M, M/L
색상	Dark Red / Grenadine
프레임	Advanced-Grade Composite, 12x142mm thru-axle, disc, flip chip dropout
포크	Advanced SL-Grade Composite, full-composite OverDrive steerer, 12mm thru-axle, disc
서스펜션	N/A
부품	
핸들바	Giant Contact SLR XR D-Fuse, 31.8mm XS:42cm, S:42cm, M:44cm, M/L:44cm, L:46cm, XL:46cm
GRIPS	Stratus Lite 3.0
스텝	Giant Contact, 8-degree XS:50mm, S:60mm, M:70mm, M/L:80mm, L:80mm, XL:90mm
싯포스트	Giant D-Fuse SLR, composite, -5/+15mm offset
안장	Giant Approach SL
페달	N/A
구동계	
변속기	Shimano GRX RX-815 Di2, 2x11
앞 변속기	Shimano GRX RX-815 Di2
뒷 변속기	Shimano GRX RX-815 Di2
브레이크	Shimano GRX RX-810 hydraulic, Shimano SM-RT800 rotors [F]160mm, [R]160mm
브레이크 레버	Shimano GRX RX-810 hydraulic
스프라켓	Shimano CS-HG800, 11-speed, 11x34
체인	KMC X11SL-1
크랭크 셋	Shimano GRX RX-810, 31/48 XS:170mm, S:170mm, M:172.5mm, M/L:172.5mm, L:175mm, XL:175mm
BB	Shimano, press fit

바퀴	
휠	Giant CXR 1 Carbon Disc WheelSystem
허브	Giant CXR 1 Carbon Disc WheelSystem
스포크	Giant CXR 1 Carbon Disc WheelSystem
타이어	Maxxis Receptor, 700x40c, tubeless
추가 기능	tubeless prepared, 53mm max tire size in "long" flip chip position, 42mm max tire size in "short" flip chip position

가격: ₩5,990,000

지오메트리

프레임	XS	S	M	ML
	SHORT LONG	SHORT LONG	SHORT LONG	SHORT LONG
시트 튜브 길이 (mm)	430	450	470	490
시트 튜브 각도	74.0°	73.5°	73.5°	73.0°
탐튜브 길이 (mm)	540	550	560	575
헤드 튜브 길이 (mm)	125	135	150	165
헤드 튜브 각도	70.0°	71.0°	71.5°	72.0°
포크 레이크 (mm)	50	50	50	50
트레일 (mm)	78 82	72 75	68 72	65 68
휠베이스 (mm)	1024 1034	1020 1030	1026 1036	1031 1041
체인스테이 길이 (mm)	425 435	425 435	425 435	425 435
BB (mm)	80 81	80 81	80 81	80 81
스택 (mm)	556	570	586	602
범위 (mm)	381	381	387	391
스탠드 오버 (mm)	724 731	740 747	757 764	774 780
핸들바 폭 (mm)	420	420	440	440
스텝 길이 (mm)	50	60	70	80
크랭크 길이 (mm)	170	170	172.5	172.5
휠사이즈	700C	700C	700C	700C

상기 스펙은 글로벌 스펙이며, 실제 구성과 차이가 있을 수 있습니다. 정확한 스펙은 매장을 방문하여 확인해주시기 바랍니다.