

리볼트 어드밴스 PRO 1

GIANT



스펙

프레임	
사이즈	XS, S, M, M/L
색상	Blue Dragonfly/Chrome
프레임	Advanced-grade composite, 12x142mm thru-axle, disc, flip chip dropout
포크	Advanced SL-grade composite, full-composite OverDrive steerer, 12mm thru-axle, disc
서스펜션	N/A
부품	
핸들바	Giant Contact SLR XR D-Fuse, 31.8mm XS:42cm, S:42cm, M:44cm, M/L:44cm
GRIPS	Stratus Lite 3.0
스텝	Giant Contact, 8-degree XS:50mm, S:60mm, M:70mm, M/L:80mm
싯포스트	Giant D-Fuse SLR, composite, -5/+15mm offset
안장	Giant Approach SL
페달	N/A
구동계	
변속기	SRAM Rival eTap AXS, 2x12
앞 변속기	SRAM Rival eTap AXS
뒷 변속기	SRAM Rival eTap AXS
브레이크	SRAM Rival eTap AXS hydraulic, SRAM PaceLine rotors [F]160mm, [R]160mm
브레이크 레버	SRAM Rival eTap AXS hydraulic
스프라켓	SRAM Rival, 12-speed, 10x36
체인	SRAM Rival D1
크랭크 셋	SRAM Rival D1 DUB, 30/43 XS:170mm, S:170mm, M:172.5mm, M/L:172.5mm
BB	SRAM DUB, press fit

바퀴	
휠	Giant CXR 1 Carbon Disc WheelSystem, [F] 35mm, [R] 35mm
허브	[F] Giant AR alloy, CenterLock, 12mm thru-axle, [R] Giant AR alloy, DT350 36t ratchet driver, CenterLock, 12mm thru-axle
스포크	Sapim CX-Ray
타이어	CADEX AR, 700x40c, tubeless
추가 기능	tubeless prepared, 53mm max tire size in "long" flip chip position, 45mm max tire size in "short" flip chip position

가격: ₩6,590,000

지오메트리

프레임	XS		S		M		ML	
	SHORT	LONG	SHORT	LONG	SHORT	LONG	SHORT	LONG
시트 튜브 길이 (mm)	430	450	470	490				
시트 튜브 각도	74.0°	73.5°	73.5°	73.0°				
탑튜브 길이 (mm)	540	550	560	575				
헤드 튜브 길이 (mm)	125	135	150	165				
헤드튜브 각도	70.0°	71.0°	71.5°	72.0°				
포크 레이크 (mm)	50	50	50	50				
트레일 (mm)	78 82	72 75	68 72	65 68				
휠베이스 (mm)	1024 1034	1020 1030	1026 1036	1031 1041				
체인스테이 길이 (mm)	425 435	425 435	425 435	425 435				
BB (mm)	80 81	80 81	80 81	80 81				
스택 (mm)	556	570	586	602				
범위 (mm)	381	381	387	391				
스탠드 오버 (mm)	724 731	740 747	757 764	774 780				
핸들바 폭 (mm)	420	420	440	440				
스텝 길이 (mm)	50	60	70	80				
크랭크 길이 (mm)	170	170	172.5	172.5				
휠사이즈	700C	700C	700C	700C				

상기 스펙은 글로벌 스펙이며, 실제 구성과 차이가 있을 수 있습니다. 정확한 스펙은 매장을 방문하여 확인해주시기 바랍니다.