

티씨알 어드밴스 PRO DISC 0 AR



스펙

프레임	
사이즈	XS, S, M, M/L
색상	Matte Carbon/Gloss Messier
프레임	Advanced-Grade Composite, disc
포크	Advanced-Grade Composite, full-composite OverDrive 2 steerer, disc
서스펜션	N/A
부품	
핸들바	Giant Contact SLR XS:40cm, S:40cm, M:42cm, M/L:42cm, L:44cm, XL:44cm
GRIPS	Stratus Lite 3.0
스텝	Giant Contact SL XS:80mm, S:90mm, M:100mm, M/L:110mm, L:110mm, XL:120mm
싯포스트	Giant Variant, composite, -5/+15mm offset
안장	Giant Fleet SL
페달	N/A
구동계	
변속기	SRAM Force eTap AXS with Blips
앞 변속기	SRAM Force eTap AXS
뒷 변속기	SRAM Force eTap AXS
브레이크	SRAM Force eTap AXS hydraulic, SRAM CenterLine XR rotors [F]160mm, [R]160mm
브레이크 레버	SRAM Force eTap AXS hydraulic
스프라켓	SRAM Force, 12-speed, 10x36
체인	SRAM Force D1
크랭크 셋	SRAM Force D1 DUB, 33/46with Power Halo power meter XS:170mm, S:170mm, M:172.5mm, M/L:172.5mm, L:175mm, XL:175mm
BB	SRAM DUB, press fit

바퀴	
휠	Giant SLR 1 36 Carbon Disc WheelSystem, [F] 36mm, [R] 36mm
허브	[F] Giant Low Friction Hub, CenterLock, 12mm thru-axle, [R] Giant Low Friction Hub, 30t ratchet driver, CenterLock, 12mm thru-axle
스포크	Sapim CX-Ray
타이어	CADEX Classic, tubeless, 700x28c (32mm), folding
추가 기능	computer mount, tubeless prepared, 32mm max tire size

가격: ₩9,100,000

지오메트리

프레임	XS	S	M	ML
시트 튜브 길이 (mm)	425	445	470	500
시트 튜브 각도	74.5°	74.0°	73.5°	73.0°
탑튜브 길이 (mm)	520	535	550	565
헤드 튜브 길이 (mm)	120	130	145	165
헤드 튜브 각도	71.0°	72.3°	73.0°	73.0°
포크 레이크 (mm)	45	45	45	45
트레일 (mm)	72.1	64	59.2	59.2
휠베이스 (mm)	976	977	980	991
체인스테이 길이 (mm)	405	405	405	405
BB (mm)	72	70	70	67
스택 (mm)	517	528	545	562
범위 (mm)	376	383	388	393
스탠드 오버 (mm)	706	725	747	773
핸들바 폭 (mm)	400	400	420	420
스텝 길이 (mm)	80	90	100	110
크랭크 길이 (mm)	170	170	172.5	172.5
휠사이즈	700C	700C	700C	700C

상기 스펙은 글로벌 스펙이며, 실제 구성과 차이가 있을 수 있습니다. 정확한 스펙은 매장을 방문하여 확인해주시기 바랍니다.