

티씨알 어드밴스 PRO DISC 0 DI2

GIANT



스펙

프레임	
사이즈	XS, S, M, M/L, L
색상	Blue Dragonfly/Chrome, Carbon
프레임	Advanced-grade composite, disc
포크	Advanced-grade composite, full-composite OverDrive 2 steerer, disc
서스펜션	N/A
부품	
핸들바	Giant Contact SLR XS:40cm, S:40cm, M:42cm, M/L:42cm, L:44cm
GRIPS	Stratus Lite 2.0
스텝	Giant Contact SL XS:80mm, S:90mm, M:100mm, M/L:110mm, L:110mm
시프스트	Giant Variant, composite, -5/+15mm offset
안장	Giant Fleet SL
페달	N/A
구동계	
변속기	Shimano Ultegra Di2 ST-R8170
앞 변속기	Shimano Ultegra Di2 FD-R8150
뒷 변속기	Shimano Ultegra Di2 RD-R8150
브레이크	Shimano Ultegra Di2 hydraulic, Shimano RT-CL800 rotors [F]160mm, [R]140mm
브레이크 레버	Shimano Ultegra Di2 hydraulic
스프라켓	Shimano Ultegra, 12-speed, 11x34
체인	Shimano Ultegra
크랭크 셋	Shimano Ultegra, 36/52 with Giant Power Pro power meter XS:170mm, S:170mm, M:172.5mm, M/L:172.5mm, L:175mm
BB	Shimano, press fit

바퀴	
휠	Giant SLR 1 36 Carbon Disc WheelSystem, [F] 36mm, [R] 36mm
허브	[F] Giant Low Friction Hub, CenterLock, 12mm thru-axle [R] Giant Low Friction Hub, 30t ratchet driver, CenterLock, 12mm thru-axle
스포크	Sapim CX-Ray
타이어	CADEX Race, tubeless, 700x25c (26.5mm), folding
추가 기능	computer mount, tubeless prepared, 32mm max tire size

가격: ₩7,190,000

지오메트리

프레임	XS	S	M	ML	L
시트 튜브 길이 (mm)	425	445	470	500	530
시트 튜브 각도	74.5°	74.0°	73.5°	73.0°	73.0°
탑튜브 길이 (mm)	520	535	550	565	580
헤드 튜브 길이 (mm)	120	130	145	165	185
헤드 튜브 각도	71.0°	72.3°	73.0°	73.0°	73.0°
포크 레이크 (mm)	45	45	45	45	45
트레일 (mm)	72.1	64	59.2	59.2	59.2
휠베이스 (mm)	976	977	980	991	1006
체인스테이 길이 (mm)	405	405	405	405	405
BB (mm)	72	70	70	67	67
스택 (mm)	517	528	545	562	581
범위 (mm)	376	383	388	393	402
스탠드 오버 (mm)	706	725	747	773	800
핸들바 폭 (mm)	400	400	420	420	440
스텝 길이 (mm)	80	90	100	110	110
크랭크 길이 (mm)	170	170	172.5	172.5	175
휠사이즈	700C	700C	700C	700C	700C

상기 스펙은 글로벌 스펙이며, 실제 구성과 차이가 있을 수 있습니다. 정확한 스펙은 매장을 방문하여 확인해주시기 바랍니다.