



SPECS

| ΣΚΕΛΕΤΟΣ | |
|---------------------|---|
| ΜΕΓΕΘΗ | XS, S, M, M/L, L, XL |
| ΧΡΩΜΑΤΑ | Meteorite Mist, Icicle White |
| ΣΚΕΛΕΤΟΣ | Advanced-grade Composite, 12x142mm thru-axle, disc |
| ΠΙΡΟΥΝΙ | Advanced-grade Composite, full-composite OverDrive Aero steerer, 12x100mm thru-axle, disc |
| ΕΞΑΡΤΗΜΑΤΑ | |
| ΤΙΜΟΝΙ | Giant Contact SL Aero XS:38cm, S:38cm, M:40cm, M/L:40cm, L:42cm, XL:42cm |
| GRIPS | Stratus Lite 2.0 |
| ΛΑΙΜΟΣ ΤΙΜΟΝΙΟΥ | Giant Contact SL Aero XS:80mm, S:90mm, M:100mm, M/L:110mm, L:110mm, XL:120mm |
| ΛΑΙΜΟΣ ΣΈΛΛΑΣ | Giant Vector, composite, -5/+15mm offset |
| ΣΈΛΛΑ | Giant Fleet SL |
| ΜΕΤΑΔΟΣΗ | |
| ΛΕΒΙΕ ΤΑΧΥΤΗΤΩΝ | Shimano 105 Di2 |
| ΝΤΕΡΑΓΊΕΡ ΕΜΠΡΟΣΘΙΟ | Shimano 105 Di2 |
| ΝΤΕΡΑΓΊΕΡ ΟΠΙΣΘΙΟ. | Shimano 105 Di2 |
| ΦΡΈΝΑ | Shimano 105 Di2 hydraulic, Shimano RT-CL700 rotors [F]160mm, [R]140mm |
| ΜΑΝΊΤΤΕΣ ΦΡΈΝΩΝ | Shimano 105 Di2 hydraulic |
| CASETTE Ή ΕΛΕΥΘΕΡΟ | Shimano 105, 12-speed, 11x34 |
| ΑΛΥΣΙΔΑ | KMC X12L-1 |
| ΔΙΣΚΟΒΡΑΧΙΩΝΑΣ | Shimano 105, 36/52 XS:165mm, S:165mm, M:170mm, M/L:170mm, L:172.5mm, XL:172.5mm |
| BOTTOM BRACKET | Shimano, press fit |

| WHEELS | |
|--------------------|---|
| ΣΤΕΦΑΝΙΑ | Giant SLR 2 50 Carbon Disc WheelSystem, [F]50mm, [R]50mm |
| ΚΕΝΤΡΑ | [F] Giant alloy, CenterLock, 12mm thru-axle, [R] Giant alloy, pawl driver(3-pawl 30T), CenterLock, 12mm thru-axle |
| ΑΚΤΙΝΕΣ | Sapim |
| ΕΛΑΣΤΙΚΑ | Giant Gavia Course 0, tubeless, 700x28c, folding |
| EXTRAS | computer mount, water bottle cages, tubeless prepared, 32mm max tire size |
| LIMITS | |
| MAX TIRE CLEARANCE | 32mm |

ΓΕΩΜΕΤΡΙΑ

| ΣΚΕΛΕΤΟΣ | XS | S | M | ML | L | XL |
|--------------------------|-------|-------|-------|-------|-------|-------|
| Seat Tube Length (mm) | 465 | 500 | 520 | 545 | 575 | 595 |
| Seat Tube Angle | 74,5° | 74,0° | 73,5° | 73,0° | 73,0° | 72,5° |
| Top Tube Length (mm) | 520 | 535 | 550 | 565 | 580 | 600 |
| Head Tube Length (mm) | 120 | 130 | 145 | 165 | 185 | 200 |
| Head Tube Angle | 71,0° | 72,3° | 73,0° | 73,0° | 73,0° | 73,0° |
| Fork Rake (mm) | 45 | 45 | 45 | 45 | 45 | 45 |
| Trail (mm) | 70,5 | 62,5 | 57,8 | 57,8 | 57,8 | 57,8 |
| Wheelbase (mm) | 976 | 977 | 980 | 991 | 1006 | 1020 |
| Chain Stay Length (mm) | 405 | 405 | 405 | 405 | 405 | 405 |
| Bottom Bracket Drop (mm) | 72 | 70 | 70 | 67 | 67 | 67 |
| Stack (mm) | 517 | 528 | 545 | 562 | 581 | 596 |
| Reach (mm) | 376 | 383 | 388 | 393 | 402 | 412 |
| Stand Over Height (mm) | 722 | 753 | 770 | 794 | 821 | 834 |
| Handlebar Width (mm) | 380 | 380 | 400 | 400 | 420 | 420 |
| Stem Length (mm) | 80 | 90 | 100 | 110 | 110 | 120 |
| Crank Length (mm) | 165 | 165 | 170 | 170 | 172,5 | 172,5 |

Όλες οι προδιαγραφές είναι δυνατό να αλλάξουν χωρίς πρότερη ειδοποίηση