

PROPEL ADVANCED 1



SPECS

FRAME	
SIZES	XS, S, M, M/L, L, XL
COLORS	Meteorite Mist, Icicle White
FRAME	Advanced-grade Composite, 12x142mm thru-axle, disc
FORK	Advanced-grade Composite, full-composite OverDrive Aero steerer, 12x100mm thru-axle, disc
COMPONENTS	
HANDLEBAR	Giant Contact SL Aero XS:38cm, S:38cm, M:40cm, M/L:40cm, L:42cm, XL:42cm
GRIPS	Stratus Lite 2.0
STEM	Giant Contact SL Aero XS:80mm, S:90mm, M:100mm, M/L:110mm, L:110mm, XL:120mm
SEATPOST	Giant Vector, composite, -5/+15mm offset
SADDLE	Giant Fleet SL
DRIVETRAIN	
SHIFTERS	Shimano 105 Di2
FRONT DERAILLEUR	Shimano 105 Di2
REAR DERAILLEUR	Shimano 105 Di2
BRAKES	Shimano 105 Di2 hydraulic, Shimano RT-CL700 rotors [F]160mm, [R]140mm
BRAKE LEVERS	Shimano 105 Di2 hydraulic
CASSETTE	Shimano 105, 12-speed, 11x34
CHAIN	KMC X12L-1
CRANKSET	Shimano 105, 36/52 XS:165mm, S:165mm, M:170mm, M/L:170mm, L:172.5mm, XL:172.5mm
BOTTOM BRACKET	Shimano, press fit

WHEELS	
RIMS	Giant SLR 2 50 Carbon Disc WheelSystem, [F]50mm, [R]50mm
HUBS	[F] Giant alloy, CenterLock, 12mm thru-axle, [R] Giant alloy, pawl driver(3-pawl 30T), CenterLock, 12mm thru-axle
SPOKES	Sapim
TIRES	Giant Gavia Course 0, tubeless, 700x28c, folding
EXTRAS	computer mount, water bottle cages, tubeless prepared, 32mm max tire size
LIMITS	
MAX TIRE CLEARANCE	32mm

Recommended Retail Price: \$5,500.00

GEOMETRY

FRAME	XS	S	M	ML	L	XL
Seat Tube Length (inch)	18.3	19.7	20.5	21.5	22.6	23.4
Seat Tube Angle	74.5°	74.0°	73.5°	73.0°	73.0°	72.5°
Top Tube Length (inch)	20.5	21.1	21.7	22.2	22.8	23.6
Head Tube Length (inch)	4.7	5.1	5.7	6.5	7.3	7.9
Head Tube Angle	71.0°	72.3°	73.0°	73.0°	73.0°	73.0°
Fork Rake (inch)	1.8	1.8	1.8	1.8	1.8	1.8
Trail (inch)	2.8	2.4	2.2	2.2	2.2	2.2
Wheelbase (inch)	38.4	38.5	38.6	39	39.6	40.2
Chain Stay Length (inch)	15.9	15.9	15.9	15.9	15.9	15.9
Bottom Bracket Drop (inch)	2.8	2.8	2.8	2.6	2.6	2.6
Stack (inch)	20.4	20.8	21.5	22.1	22.9	23.5
Reach (inch)	14.8	15.1	15.3	15.5	15.8	16.2
Stand Over Height (inch)	28.4	29.6	30.3	31.3	32.3	32.8
Handlebar Width (inch)	15	15	15.7	15.7	16.5	16.5
Stem Length (inch)	3.1	3.5	3.9	4.3	4.3	4.7
Crank Length (inch)	6.5	6.5	6.7	6.7	6.8	6.8

**All specifications and prices listed are subject to change without notice. Actual weight may vary due to manufacturing tolerances, color variations, frame size and variability in production components.*