

PROPEL ADVANCED 1

GIANT



SPECS

RAMME	
STØRRELSE	XS, S, M, M/L, L, XL
FARGE	Carbon/Stealth Chrome, Meteor Storm
RAMME	Advanced-grade Composite, 12x142mm thru-axle, disc
GAFFEL	Advanced-grade Composite, full-composite OverDrive Aero steerer, 12x100mm thru-axle, disc
KOMPONENTER	
STYRE	Giant Contact SL Aero XS:380/360mm, S:380/360mm, M:400/370mm, M/L:400/370mm, L:420/390mm, XL:420/390mm
GRIPS	Stratus Lite 2.0
STYRSTEM	Giant Contact SL Aero XS:80mm, S:90mm, M:100mm, M/L:110mm, L:110mm, XL:120mm
SETEPINNE	Giant Vector, composite, -5/+15mm offset
SADEL	Giant Fleet SL
DRIVVERK	
GIRHENDLER	Shimano 105 Di2
FRONTGIR	Shimano 105 Di2
BAKGIR	Shimano 105 Di2
BREMSE	Shimano 105 Di2 hydraulic, Shimano RT-CL700 rotors [F]160mm, [R]140mm
BREMSEHENDLER	Shimano 105 Di2 hydraulic
KASSETT	Shimano 105, 12-speed, 11x36
KJEDE	KMC X12L-1
KRANK	Shimano 105 Di2, 36/52 XS:165mm, S:165mm, M:170mm, M/L:170mm, L:172.5mm, XL:172.5mm
BOTTOM BRACKET	Shimano, press fit

HJUL	
FELG	Giant SLR 2 50 Carbon Disc WheelSystem, [F]50mm, [R]50mm
NAV	[F] Giant Aero Hub, CenterLock [R] Giant Aero Hub, 3-Pawl Driver, CenterLock 12mm thru-axle
EIKE	Sapim
DEKK	Giant Gavia Course 0, tubeless, 700x28c, folding
EXTRAS	computer mount, water bottle cages, tubeless prepared, 32mm max tire size

GEOMETRI

RAMME	XS	S	M	M/L	L	XL
Seat Tube Length (mm)	484	505	528,5	554	576	595
Seat Tube Angle	74,5°	74,0°	73,5°	73,0°	73,0°	72,5°
Top Tube Length (mm)	520	535	550	565	580	600
Head Tube Length (mm)	115	127	145	165	185	200
Head Tube Angle	71,5°	72,5°	73,0°	73,0°	73,0°	73,0°
Fork Rake (mm)	45	45	45	45	45	45
Trail (mm)	67,8	61,4	58,3	58,3	58,3	58,3
Wheelbase (mm)	971	973	980	990	1006	1020
Chain Stay Length (mm)	405	405	405	405	405	405
Bottom Bracket Drop (mm)	72	72	69,5	69,5	67	67
Stack (mm)	515	530	546	565	582	596
Reach (mm)	377	383	388	392	402	412
Stand Over Height (mm)	746	764	787	808	832	847
Handlebar Width (mm)	380	380	400	400	420	420
Stem Length (mm)	80	90	100	110	110	120
Crank Length (mm)	165	165	170	170	172,5	172,5
Wheel Size	700C	700C	700C	700C	700C	700C

Alle spesifikasjonene kan endres uten varsel.