



SPECIFIKACIJE

OKVIR	
VELIKOSTI	XS, S, M, M/L, L, XL
BARVE	Meteorite Mist, Icicle White
OKVIR	Advanced-grade Composite, 12x142mm thru-axle, disc
VILICE	Advanced-grade Composite, full-composite OverDrive Aero steerer, 12x100mm thru-axle, disc
KOMPONENTE	
KRMILO	Giant Contact SL Aero XS:38cm, S:38cm, M:40cm, M/L:40cm, L:42cm, XL:42cm
GRIPS	Stratus Lite 2.0
OPORA KRMILA	Giant Contact SL Aero XS:80mm, S:90mm, M:100mm, M/L:110mm, L:110mm, XL:120mm
OPORA SEDEŽA	Giant Vector, composite, -5/+15mm offset
SEDEŽ	Giant Fleet SL
POGON	
PRESTAVNE ROČICE	Shimano 105 Di2
PREDNJI MENJALNIK	Shimano 105 Di2
ZADNJI MENJALNIK	Shimano 105 Di2
ZAVORE	Shimano 105 Di2 hydraulic, Shimano RT-CL700 rotors [F]160mm, [R]140mm
ZAVORNE ROČICE	Shimano 105 Di2 hydraulic
VERIŽNIK	Shimano 105, 12-speed, 11x34
VERIGA	KMC X12L-1
GONILKE Z VERIŽNIKI	Shimano 105, 36/52 XS:165mm, S:165mm, M:170mm, M/L:170mm, L:172.5mm, XL:172.5mm
BOTTOM BRACKET	Shimano, press fit

OBROČNIKI	
OBROČI	Giant SLR 2 50 Carbon Disc WheelSystem, [F]50mm, [R]50mm
PESTA	[F] Giant alloy, CenterLock, 12mm thru-axle, [R] Giant alloy, pawl driver(3-pawl 30T), CenterLock, 12mm thru-axle
NAPERE	Sapim
PLAŠČI	Giant Gavia Course 0, tubeless, 700x28c, folding
DODATKI	computer mount, water bottle cages, tubeless prepared, 32mm max tire size
LIMITS	
MAX TIRE CLEARANCE	32mm

GEOMETRIJA

OKVIR	XS	S	M	ML	L	XL
Dolžina sedežne cevi (mm)	465	500	520	545	575	595
Kot sedežne cevi	74,5°	74,0°	73,5°	73,0°	73,0°	72,5°
Top Tube Length (mm)	520	535	550	565	580	600
Višina glave okvirja (mm)	120	130	145	165	185	200
Krmlini kot	71,0°	72,3°	73,0°	73,0°	73,0°	73,0°
Zamik vpetja osi (mm)	45	45	45	45	45	45
Trail (mm)	70,5	62,5	57,8	57,8	57,8	57,8
Medosna razdalja (mm)	976	977	980	991	1006	1020
Dolžina cevi ob verigi (mm)	405	405	405	405	405	405
Bottom Bracket Drop (mm)	72	70	70	67	67	67
Oddaljenost zgornje cevi od gonilne osi (mm)	517	528	545	562	581	596
Doseg (mm)	376	383	388	393	402	412
Višina zgornje cevi (mm)	722	753	770	794	821	834
Širina krmila (mm)	380	380	400	400	420	420
Dolžina opore krmila (mm)	80	90	100	110	110	120
Dolžina gonilke (mm)	165	165	170	170	172,5	172,5

Vse navedene specifikacije se lahko spremenijo brez obvestila.