

# PROPEL ADVANCED 2

**GIANT**



## SPECS

FRAME	
<b>SIZES</b>	XS, S, M, M/L, L, XL
<b>COLORS</b>	Supernova, Mach Blue
<b>FRAME</b>	Advanced-grade Composite, 12x142mm thru-axle, disc
<b>FORK</b>	Advanced-grade Composite, full-composite OverDrive Aero steerer, 12x100mm thru-axle, disc
COMPONENTS	
<b>HANDLEBAR</b>	Giant Contact SL Aero XS:38cm, S:38cm, M:40cm, M/L:40cm, L:42cm, XL:42cm
<b>GRIPS</b>	Stratus Lite 2.0
<b>STEM</b>	Giant Contact SL Aero XS:80mm, S:90mm, M:100mm, M/L:110mm, L:110mm, XL:120mm
<b>SEATPOST</b>	Giant Vector, composite, -5/+15mm offset
<b>SADDLE</b>	Giant Fleet SL
DRIVETRAIN	
<b>SHIFTERS</b>	Shimano 105
<b>FRONT DERAILLEUR</b>	Shimano 105
<b>REAR DERAILLEUR</b>	Shimano 105
<b>BRAKES</b>	Shimano 105 hydraulic, Shimano SM-RT64 rotors [F]160mm, [R]140mm
<b>BRAKE LEVERS</b>	Shimano 105 hydraulic
<b>CASSETTE</b>	Shimano 105, 12-speed, 11x34
<b>CHAIN</b>	KMC X12L-1
<b>CRANKSET</b>	Shimano 105, 36/52 XS:165mm, S:165mm, M:170mm, M/L:170mm, L:172.5mm, XL:172.5mm
<b>BOTTOM BRACKET</b>	Shimano, press fit

WHEELS	
<b>RIMS</b>	Giant P-A1 Disc, alloy
<b>HUBS</b>	Giant P-A1 Disc, 12mm thru-axle
<b>SPOKES</b>	Sapim
<b>TIRES</b>	Giant Gavia Course 0, tubeless, 700x28c, folding
<b>EXTRAS</b>	computer mount, water bottle cages, tubeless prepared, 32mm max tire size
LIMITS	
<b>MAX TIRE CLEARANCE</b>	32mm

## GEOMETRY

FRAME	XS	S	M	ML	L	XL
Seat Tube Length (mm)	465	500	520	545	575	595
Seat Tube Angle	74,5°	74,0°	73,5°	73,0°	73,0°	72,5°
Top Tube Length (mm)	520	535	550	565	580	600
Head Tube Length (mm)	120	130	145	165	185	200
Head Tube Angle	71,0°	72,3°	73,0°	73,0°	73,0°	73,0°
Fork Rake (mm)	45	45	45	45	45	45
Trail (mm)	70,5	62,5	57,8	57,8	57,8	57,8
Wheelbase (mm)	976	977	980	991	1006	1020
Chain Stay Length (mm)	405	405	405	405	405	405
Bottom Bracket Drop (mm)	72	70	70	67	67	67
Stack (mm)	517	528	545	562	581	596
Reach (mm)	376	383	388	393	402	412
Stand Over Height (mm)	722	753	770	794	821	834
Handlebar Width (mm)	380	380	400	400	420	420
Stem Length (mm)	80	90	100	110	110	120
Crank Length (mm)	165	165	170	170	172,5	172,5

All specifications listed are subject to change without notice.