

PROPEL ADVANCED 2

GIANT



SPECIFICATIES

| FRAME | |
|------------------|---|
| MATEN | XS, S, M, M/L, L, XL |
| KLEUREN | Pure Red |
| FRAME | Advanced-grade composite, disc |
| VOORVORK | Advanced-grade composite, full-composite OverDrive Aero steerer, disc |
| DEMPER | N/A |
| ONDERDELEN | |
| STUUR | Giant Contact SL Aero XS:40cm, S:40cm, M:42cm, M/L:42cm, L:44cm, XL:44cm |
| HANDVATTEN | Stratus Lite 2.0 |
| STUURPEN | Giant Contact SL Aero XS:80mm, S:90mm, M:100mm, M/L:110mm, L:110mm, XL:120mm |
| ZADELPEN | Giant Vector, composite, -5/+15mm offset |
| ZADEL | Giant Fleet SL |
| PEDALEN | N/A |
| AFMONTAGE | |
| SHIFTERS | Shimano 105 |
| VOORDERAILLEUR | Shimano 105 |
| ACHTERDERAILLEUR | Shimano 105 |
| REMMEN | Shimano 105 hydraulic, Giant MPH rotors [F]160mm, [R]140mm |
| REMHENDELS | Shimano 105 hydraulic |
| CASSETTE | Shimano 105, 12-speed, 11x34 |
| AANDRIJVING | KMC X12EL-1 |
| CRANKSET | Shimano 105, 36/52 XS:170mm, S:170mm, M:172.5mm, M/L:172.5mm, L:175mm, XL:175mm |
| BOTTOM BRACKET | Shimano, press fit |

| WIELSET | |
|--------------------|---|
| VELGEN | Giant P-A2 Disc, alloy |
| NAVEN | Giant P-A2 Disc, 12mm thru-axle |
| SPAKEN | Sapim |
| BANDEN | Giant Gavia Course 1, tubeless, 700x25c (28mm), folding |
| EXTRA'S | computer mount, water bottle cages, tubeless prepared, 32mm max tire size |
| LIMITS | |
| MAX TIRE CLEARANCE | 32mm |

Adviesprijs: € 2.999,00

GEOMETRIE

| FRAME | S | M | ML | L | XL |
|---------------------------------|-------|-------|-------|-------|-------|
| Zitbuis lengte (mm) | 500 | 520 | 545 | 575 | 595 |
| Zitbuis hoek | 74,0° | 73,5° | 73,0° | 73,0° | 72,5° |
| Frame Lengte (horizontaal) (mm) | 535 | 550 | 565 | 580 | 600 |
| Balhoofdbuis Lengte (mm) | 130 | 145 | 165 | 185 | 200 |
| Balhoofdbuis Hoek | 72,3° | 73,0° | 73,0° | 73,0° | 73,0° |
| Vork Sprong (mm) | 45 | 45 | 45 | 45 | 45 |
| Naloop (mm) | 62,5 | 57,8 | 57,8 | 57,8 | 57,8 |
| Wielbasis (mm) | 977 | 980 | 991 | 1006 | 1020 |
| Liggende achtervork lengte (mm) | 405 | 405 | 405 | 405 | 405 |
| Bottom Bracket Drop (mm) | 70 | 70 | 67 | 67 | 67 |
| Stack (mm) | 528 | 545 | 562 | 581 | 596 |
| Reach (mm) | 383 | 388 | 393 | 402 | 412 |
| Stand Over Height (mm) | 753 | 770 | 794 | 821 | 834 |
| Stuur breedte (mm) | 400 | 420 | 420 | 440 | 440 |
| Stuurpen Lengte (mm) | 90 | 100 | 110 | 110 | 120 |
| Cranklengte (mm) | 170 | 172,5 | 172,5 | 175 | 175 |
| Wielmaat | 700C | 700C | 700C | 700C | 700C |

Deze specificaties zijn met de grootste zorgvuldigheid samengesteld. Specificaties, beschikbaarheid, prijzen en kleuren kunnen echter zonder voor aankondiging wijzigen.