

PROPEL ADVANCED 2

GIANT



SPECS

RAMME	
STØRRELSE	XS, S, M, M/L, L, XL
FARGE	Supernova, Mach Blue
RAMME	Advanced-grade Composite, 12x142mm thru-axle, disc
GAFFEL	Advanced-grade Composite, full-composite OverDrive Aero steerer, 12x100mm thru-axle, disc
KOMPONENTER	
STYRE	Giant Contact SL Aero XS:38cm, S:38cm, M:40cm, M/L:40cm, L:42cm, XL:42cm
GRIPS	Stratus Lite 2.0
STYRSTEM	Giant Contact SL Aero XS:80mm, S:90mm, M:100mm, M/L:110mm, L:110mm, XL:120mm
SETEPINNE	Giant Vector, composite, -5/+15mm offset
SADEL	Giant Fleet SL
DRIVVERK	
GIRHENDLER	Shimano 105
FRONTGIR	Shimano 105
BAKGIR	Shimano 105
BREMSE	Shimano 105 hydraulic, Shimano SM-RT64 rotors [F]160mm, [R]140mm
BREMSEHENDLER	Shimano 105 hydraulic
KASSETT	Shimano 105, 12-speed, 11x34
KJEDE	KMC X12L-1
KRANK	Shimano 105, 36/52 XS:165mm, S:165mm, M:170mm, M/L:170mm, L:172.5mm, XL:172.5mm
BOTTOM BRACKET	Shimano, press fit

HJUL	
FELG	Giant P-A1 Disc, alloy
NAV	Giant P-A1 Disc, 12mm thru-axle
EIKE	Sapim
DEKK	Giant Gavia Course 0, tubeless, 700x28c, folding
EXTRAS	computer mount, water bottle cages, tubeless prepared, 32mm max tire size
LIMITS	
MAX TIRE CLEARANCE	32mm

GEOMETRI

RAMME	XS	S	M	ML	L	XL
Seat Tube Length (mm)	465	500	520	545	575	595
Seat Tube Angle	74,5°	74,0°	73,5°	73,0°	73,0°	72,5°
Top Tube Length (mm)	520	535	550	565	580	600
Head Tube Length (mm)	120	130	145	165	185	200
Head Tube Angle	71,0°	72,3°	73,0°	73,0°	73,0°	73,0°
Fork Rake (mm)	45	45	45	45	45	45
Trail (mm)	70,5	62,5	57,8	57,8	57,8	57,8
Wheelbase (mm)	976	977	980	991	1006	1020
Chain Stay Length (mm)	405	405	405	405	405	405
Bottom Bracket Drop (mm)	72	70	70	67	67	67
Stack (mm)	517	528	545	562	581	596
Reach (mm)	376	383	388	393	402	412
Stand Over Height (mm)	722	753	770	794	821	834
Handlebar Width (mm)	380	380	400	400	420	420
Stem Length (mm)	80	90	100	110	110	120
Crank Length (mm)	165	165	170	170	172,5	172,5

Alle spesifikasjonene kan endres uten varsel.