

# PROPEL ADVANCED 2

GIANT



## SPECS

RAM	
STORLEKAR	S, M, M/L, L, XL
FÄRGER	Mach Blue, White
RAM	Advanced-grade Composite, 12x142mm thru-axle, disc
GAFFEL	Advanced-grade Composite, full-composite OverDrive Aero steerer, 12x100mm thru-axle, disc
KOMPONENTER	
STYRE	Giant Contact SL Aero XS:380/360mm, S:380/360mm, M:400/370mm, M/L:400/370mm, L:420/390mm, XL:420/390mm
GREPPAR	Stratus Lite 2.0
STAM	Giant Contact SL Aero XS:80mm, S:90mm, M:100mm, M/L:110mm, L:110mm, XL:120mm
SADELSTOLPE	Giant Vector, composite, -5/+15mm offset
SADEL	Giant Fleet SL
DRIVLINA	
VÄXLAR	Shimano 105
FRAMVÄXEL	Shimano 105
BAKVÄXEL	Shimano 105
BROMSAR	Shimano 105 hydraulic, Shimano SM-RT64 rotors [F]160mm, [R]140mm
BROMSSPAKAR	Shimano 105 hydraulic
KASSETT	Shimano 105, 12-speed, 11x36
KEDJA	KMC X12L-1
VEVPARTI	Shimano 105, 36/52 XS:165mm, S:165mm, M:170mm, M/L:170mm, L:172.5mm, XL:172.5mm
BROMSREGLAGE	Shimano, press fit

HJUL	
FÄLGAR	Giant P-A1 Disc, alloy
NAV	Giant P-A1 Disc, 12mm thru-axle
EKRAR	Stainless
DÄCK	Giant Gavia Course 0, tubeless, 700x28c, folding
EXTRAFUNKTIONER	computer mount, water bottle cages, tubeless prepared, 32mm max tire size

Price: 35 990,00 kr

## GEOMETRY

RAM	S	M	M/L	L	XL
Längd sadelrör (mm)	505	528,5	554	576	595
Vinkel sadelrör	74,0°	73,5°	73,0°	73,0°	72,5°
Topprörets längd (mm)	535	550	565	580	600
Styrhuvud Längd (mm)	127	145	165	185	200
Vinkel styrhuvud	72,5°	73,0°	73,0°	73,0°	73,0°
Gaffelvinkel (mm)	45	45	45	45	45
Spår (mm)	61,4	58,3	58,3	58,3	58,3
Hjulbas (mm)	973	980	990	1006	1020
Kedjestagslängd (mm)	405	405	405	405	405
Nedre fäste Drop (mm)	72	69,5	69,5	67	67
Stack (mm)	530	546	565	582	596
Reach (mm)	383	388	392	402	412
Stå över höjden (mm)	764	787	808	832	847
Styrets bredd (mm)	380	400	400	420	420
Stamlängd (mm)	90	100	110	110	120
Vevlängd (mm)	165	170	170	172,5	172,5
Hjulstorlek	700C	700C	700C	700C	700C

All specifications listed are subject to change without notice.