

# PROPEL ADVANCED PRO 0-AXS

**GIANT**



## SPECS

| FRAME                   |  |
|-------------------------|--|
| <b>SIZES</b>            | XS, S, M, M/L, L, XL   |
| <b>COLOURS</b>          | Obsidian Pulse   |
| <b>FRAME</b>            | Advanced-grade composite, UDH, 12x142mm thru-axle, disc  |
| <b>FORK</b>             | Advanced SL-grade Composite, full-composite OverDrive Aero steerer, 12x100mm thru-axle, disc                         |
| COMPONENTS              |  |
| <b>HANDLEBAR</b>        | Giant Contact SLR 0 Aero Integrated XS:380/360mm, S:380/360mm, M:400/370mm, M/L:400/370mm, L:420/390mm, XL:420/390mm |
| <b>GRIPS</b>            | Stratus Lite 2.0   |
| <b>STEM</b>             | Giant Contact SLR 0 Aero Integrated XS:80mm, S:90mm, M:100mm, M/L:110mm, L:110mm, XL:120mm                           |
| <b>SEATPOST</b>         | Giant Vector, composite, -5/+15mm offset   |
| <b>SADDLE</b>           | Giant Fleet SL   |
| DRIVETRAIN              |  |
| <b>SHIFTERS</b>         | SRAM Force AXS E1  |
| <b>FRONT DERAILLEUR</b> | SRAM Force AXS E1  |
| <b>REAR DERAILLEUR</b>  | SRAM Force AXS E1  |
| <b>BRAKES</b>           | SRAM Force E1 hydraulic, SRAM PaceLine X rotors [F]160mm, [R]140mm   |
| <b>BRAKE LEVERS</b>     | SRAM Force AXS E1  |
| <b>CASSETTE</b>         | SRAM Force, 12-speed, 10x33  |
| <b>CHAIN</b>            | SRAM Force E1  |
| <b>CRANKSET</b>         | SRAM Force E1 DUB, 35/48 with power meter XS:165mm, S:165mm, M:170mm, M/L:170mm, L:172.5mm, XL:172.5mm               |
| <b>BOTTOM BRACKET</b>   | SRAM, press fit  |

| WHEELS        |  |
|---------------|--|
| <b>RIMS</b>   | Giant SLR 0 50 Carbon WheelSystem, [F]50mm, [R]50mm  |
| <b>HUBS</b>   | [F] Giant Aero Hub, CenterLock [R] Giant Aero Hub, 40T ratchet driver, CenterLock 12mm thru-axle |
| <b>SPOKES</b> | Aero Carbon  |
| <b>TYRES</b>  | CADEX Aero, tubeless, 700x28c (28mm), folding  |
| <b>EXTRAS</b> | computer mount, water bottle cages, tubeless prepared, 32mm max tire size                        |

**Price: €7,199.00**

## GEOMETRY

| FRAME                    | S     | M     | M/L   | L     | XL    |
|--------------------------|-------|-------|-------|-------|-------|
| Seat Tube Length (mm)    | 505   | 528.5 | 554   | 576   | 595   |
| Seat Tube Angle          | 74.0° | 73.5° | 73.0° | 73.0° | 72.5° |
| Top Tube Length (mm)     | 535   | 550   | 565   | 580   | 600   |
| Head Tube Length (mm)    | 127   | 145   | 165   | 185   | 200   |
| Head Tube Angle          | 72.5° | 73.0° | 73.0° | 73.0° | 73.0° |
| Fork Rake (mm)           | 45    | 45    | 45    | 45    | 45    |
| Trail (mm)               | 61.4  | 58.3  | 58.3  | 58.3  | 58.3  |
| Wheelbase (mm)           | 973   | 980   | 990   | 1006  | 1020  |
| Chain Stay Length (mm)   | 405   | 405   | 405   | 405   | 405   |
| Bottom Bracket Drop (mm) | 72    | 69.5  | 69.5  | 67    | 67    |
| Stack (mm)               | 530   | 546   | 565   | 582   | 596   |
| Reach (mm)               | 383   | 388   | 392   | 402   | 412   |
| Stand Over Height (mm)   | 764   | 787   | 808   | 832   | 847   |
| Handlebar Width (mm)     | 380   | 400   | 400   | 420   | 420   |
| Stem Length (mm)         | 90    | 100   | 110   | 110   | 120   |
| Crank Length (mm)        | 165   | 170   | 170   | 172.5 | 172.5 |
| Wheel Size               | 700C  | 700C  | 700C  | 700C  | 700C  |

*All specifications listed are subject to change without notice.*