

PROPEL ADVANCED PRO 0 (AXS)*



SPECS

FRAME	
SIZES	XS, S, M, M/L, L, XL
COLORS	Prismatic Haze
FRAME	Advanced-Grade Composite, disc
FORK	Advanced SL-Grade Composite, full-composite OverDrive Aero steerer, disc
COMPONENTS	
HANDLEBAR	Giant Contact SLR Aero XS:38cm, S:38cm, M:40cm, M/L:40cm, L:42cm, XL:42cm
GRIPS	Stratus Lite 2.0
STEM	Giant Contact SL Aero XS:80mm, S:90mm, M:100mm, M/L:110mm, L:110mm, XL:120mm
SEATPOST	Giant Vector, composite, -5/+15mm offset
SADDLE	Giant Fleet SL
PEDALS	N/A
DRIVETRAIN	
SHIFTERS	SRAM Force AXS HRD, ED-Force-E1
FRONT DERAILLEUR	SRAM Force AXS, FD-Force-E-E1
REAR DERAILLEUR	SRAM Force AXS, RD-Force-E-E1
BRAKES	SRAM Force AXS HRD, ED-Force-E1, SRAM PaceLine X rotors [F]160mm, [R]140mm
BRAKE LEVERS	SRAM Force AXS HRD, ED-Force-E1
CASSETTE	SRAM Force E1 XG-1270, 12-speed, 10-33
CHAIN	SRAM Force-E1, 12-speed
CRANKSET	SRAM Force E1, DUB, 35/48 with power meter XS:165mm, S:165mm, M:170mm, M/L:170mm, L:172.5mm, XL:172.5mm
BOTTOM BRACKET	SRAM DUB, Press Fit

WHEELS	
RIMS	Giant SLR 1 50 Carbon Disc WheelSystem, [F]50mm, [R]50mm
HUBS	[F] Giant Low Friction Hub, CenterLock, 12mm thru-axle [R] Giant Low Friction Hub, 30t ratchet driver, CenterLock, 12mm thru-axle
SPOKES	Sapim CX-Ray
TIRES	CADEX Race, tubeless, 700x28c (26.5mm), folding
EXTRAS	Computer mount, water bottle cages, tubeless prepared, 30mm max tyre size
LIMITS	
MAX TIRE CLEARANCE	30 mm

Price: \$9,499.00

GEOMETRY

FRAME	XS	S	M	ML	L	XL
Seat Tube Length (mm)	465	500	520	545	575	595
Seat Tube Angle	74.5°	74.0°	73.5°	73.0°	73.0°	72.5°
Top Tube Length (mm)	520	535	550	565	580	600
Head Tube Length (mm)	120	130	145	165	185	200
Head Tube Angle	71.0°	72.3°	73.0°	73.0°	73.0°	73.0°
Fork Rake (mm)	45	45	45	45	45	45
Trail (mm)	70.5	62.5	57.8	57.8	57.8	57.8
Wheelbase (mm)	976	977	980	991	1006	1020
Chain Stay Length (mm)	405	405	405	405	405	405
Bottom Bracket Drop (mm)	72	70	70	67	67	67
Stack (mm)	517	528	545	562	581	596
Reach (mm)	376	383	388	393	402	412
Stand Over Height (mm)	722	753	770	794	821	834
Stem Length (mm)	80	90	100	110	110	120
Crank Length (mm)	165	165	170	170	172.5	172.5

Please note that our specifications may be impacted by running substitution changes, we highly recommend confirming the specifications of our products with your local retailer at the time of sale if purchasing in-store. *Recommended Retail Prices are subject to change without notice and may vary from store to store depending on freight and assembly costs.