

PROPEL ADVANCED PRO 0 AXS

GIANT



SPECIFICATIES

FRAME	
MATEN	XS, S, M, M/L, L, XL
KLEUREN	Black Currant/Chrome
FRAME	Advanced-Grade Composite, disc
VOORVORK	Advanced SL-Grade Composite, full-composite OverDrive Aero steerer, disc
DEMPER	N/A
ONDERDELEN	
STUUR	Giant Contact SLR Aero XS:40cm, S:40cm, M:42cm, M/L:42cm, L:44cm, XL:44cm
HANDVATTEN	Stratus Lite 2.0
STUURPEN	Giant Contact SL Aero, OverDrive Aero XS:80mm, S:90mm, M:100mm, M/L:110mm, L:110mm, XL:120mm
ZADELPEEN	Giant Vector, composite, -5/+15mm offset
ZADEL	Giant Fleet SL
PEDALEN	N/A
AFMONTAGE	
SHIFTERS	SRAM Force eTap AXS
VOORDERAILLEUR	SRAM Force eTap AXS
ACHTTERDERAILLEUR	SRAM Force eTap AXS
REMMEN	SRAM Force eTap AXS hydraulic, SRAM CenterLine XR rotors [F]160mm, [R]140mm
REMHENDELS	SRAM Force eTap AXS hydraulic
CASSETTE	SRAM Force, 12-speed, 10x28
AANDRIJVING	SRAM Force D1
CRANKSET	SRAM Force D1 DUB, 35/48 with Giant Power Halo power meter XS:170mm, S:170mm, M:172.5mm, M/L:172.5mm, L:175mm, XL:175mm
BOTTOM BRACKET	SRAM DUB, press fit

WIELSET	
VELGEN	Giant SLR 1 50 Carbon Disc WheelSystem, [F]50mm, [R]50mm
NAVEN	[F] Giant Low Friction Hub, CenterLock, 12mm thru-axle, [R] Giant Low Friction Hub, 30t ratchet driver, CenterLock, 12mm thru-axle,
SPAKEN	SAPIM CX-Ray
BANDEN	CADEX Race, tubeless, 700x25c (26.5mm), folding
EXTRA'S	computer mount, water bottle cages, tubeless prepared, 32mm max tire size
LIMITS	
MAXIMALE BANDENVRIJHEID	32mm

Adviesprijs: € 6.999,00

GEOMETRIE

FRAME	XS	S	M	ML	L	XL
Zitbuis Lengte (mm)	465	500	520	545	575	595
Seat Post Insertion Depth (mm)	70	70	70	70	70	70
Zitbuis Hoek	74,5°	74,0°	73,5°	73,0°	73,0°	72,5°
Frame Lengte (horizontaal) (mm)	520	535	550	565	580	600
Balhoofdbuis Lengte (mm)	120	130	145	165	185	200
Balhoofdbuis Hoek	71,0°	72,3°	73,0°	73,0°	73,0°	73,0°
Vork Sprong (mm)	45	45	45	45	45	45
Naloop (mm)	70,5	62,5	57,8	57,8	57,8	57,8
Wielbasis (mm)	976	977	980	991	1006	1020
Liggende achtersvork lengte (mm)	405	405	405	405	405	405
Bottom Bracket Drop (mm)	72	70	70	67	67	67
Stack (mm)	517	528	545	562	581	596
Reach (mm)	376	383	388	393	402	412
Stand Over Height (mm)	722	753	770	794	821	834
Stuur breedte (mm)	400	400	420	420	440	440
Stuurpen Lengte (mm)	80	90	100	110	110	120
Cranklengte (mm)	170	170	172,5	172,5	175	175
Wielmaat	700C	700C	700C	700C	700C	700C

Deze specificaties zijn met de grootste zorgvuldigheid samengesteld. Specificaties, beschikbaarheid, prijzen en kleuren kunnen echter zonder vooraankondiging wijzigen.