

# PROPEL ADVANCED PRO 0-AXS

**GIANT**



## SPECS

TELAIO	
<b>TAGLIE</b>	XS, S, M, M/L, L, XL
<b>COLORAZIONI</b>	Obsidian Pulse
<b>TELAIO</b>	Advanced-grade Composite, 12x142mm thru-axle, disc
<b>FORCELLA</b>	Advanced SL-grade Composite, full-composite OverDrive Aero steerer, 12x100mm thru-axle, disc
COMPONENTISTICA	
<b>MANUBRIO</b>	Giant Contact SLR 0 Aero Integrated XS:380/360mm, S:380/360mm, M:400/370mm, M/L:400/370mm, L:420/390mm, XL:420/390mm
<b>MANOPOLE</b>	Stratus Lite 2.0
<b>ATTACCO MANUBRIO</b>	Giant Contact SLR 0 Aero Integrated XS:80mm, S:90mm, M:100mm, M/L:110mm, L:110mm, XL:120mm
<b>REGGISELLA</b>	Giant Vector, composite, -5/+15mm offset
<b>SELLA</b>	Giant Fleet SL
SISTEMA DI TRASMISSIONE	
<b>CAMBIO</b>	SRAM Force AXS E1
<b>DERAGLIATORE ANTERIORE</b>	SRAM Force AXS E1
<b>DERAGLIATORE POSTERIORE</b>	SRAM Force AXS E1
<b>FRENI</b>	SRAM Force E1 hydraulic, SRAM PaceLine X rotors [F]160mm, [R]140mm
<b>COMANDI FRENO</b>	SRAM Force AXS E1
<b>PACCO PIGNONI</b>	SRAM Force, 12-speed, 10x33
<b>CATENA</b>	SRAM Force E1
<b>GUARNITURA</b>	SRAM Force E1 DUB, 35/48 with power meter XS:165mm, S:165mm, M:170mm, M/L:170mm, L:172.5mm, XL:172.5mm
<b>MOVIMENTO CENTRALE</b>	SRAM, press fit

RUOTE	
<b>CERCHI</b>	Giant SLR 0 50 Carbon WheelSystem, [F]50mm, [R]50mm
<b>MOZZI</b>	[F] Giant Aero Hub, CenterLock [R] Giant Aero Hub, 40T ratchet driver, CenterLock 12mm thru-axle
<b>RAGGI</b>	Aero Carbon
<b>COPERTONI</b>	CADEX Aero, tubeless, 700x28c (28mm), folding
<b>EXTRA</b>	computer mount, water bottle cages, tubeless prepared, 32mm max tire size

**Prezzo: 6.699,00 €**

## GEOMETRIA

TELAIO	XS	S	M	M/L	L	XL
Lunghezza Tubo Sella (mm)	484	505	528,5	554	576	595
Angolo Tubo Sella	74,5°	74,0°	73,5°	73,0°	73,0°	72,5°
Lunghezza Tubo Orizzontale (mm)	520	535	550	565	580	600
Lunghezza Tubo Sterzo (mm)	115	127	145	165	185	200
Angolo Sterzo	71,5°	72,5°	73,0°	73,0°	73,0°	73,0°
Rake Forcella (mm)	45	45	45	45	45	45
Avancorsa (mm)	67,8	61,4	58,3	58,3	58,3	58,3
Interasse (mm)	971	973	980	990	1006	1020
Lunghezza Carro Posteriore (mm)	405	405	405	405	405	405
Drop Movimento Centrale (mm)	72	72	69,5	69,5	67	67
Stack (mm)	515	530	546	565	582	596
Reach (mm)	377	383	388	392	402	412
Altezza stand over (mm)	746	764	787	808	832	847
Larghezza Manubrio c/c (mm)	380	380	400	400	420	420
Lunghezza Attacco Manubrio (mm)	80	90	100	110	110	120
Lunghezza Pedivella (mm)	165	165	170	170	172,5	172,5
Dimensione Ruote	700C	700C	700C	700C	700C	700C

*Le specifiche tecniche e i colori sono soggette a variazioni senza obbligo di preavviso. Verifica la disponibilità con il tuo rivenditore Giant e Liv di fiducia.*