

# PROPEL ADVANCED PRO 0 (AXS)

**GIANT**



## SPECS

CADRU	
MARIMI	XS, S, M, M/L, L, XL
CULORI	Ocean Twilight/Chrome
CADRU	Advanced-grade Composite, 12x142mm thru-axle, disc
FURCA	Advanced SL-grade Composite, full-composite OverDrive Aero steerer, 12x100mm thru-axle, disc
COMPONENTE	
GHIDON	Giant Contact SLR Aero XS:38cm, S:38cm, M:40cm, M/L:40cm, L:42cm, XL:42cm
GRIPS	Stratus Lite 2.0
PIPA	Giant Contact SL Aero XS:80mm, S:90mm, M:100mm, M/L:110mm, L:110mm, XL:120mm
TIJA SA	Giant Vector, composite, -5/+15mm offset
SA	Giant Fleet SL
SISTEMUL DE SCHIMBARE A VITEZELOR	
MANETE SCHIMBATOR	SRAM Force AXS E1
SCHIMBATOR FATA	SRAM Force AXS E1
SCHIMBATOR SPATE	SRAM Force AXS E1
FRANE	SRAM Force E1 hydraulic, SRAM PaceLine X rotors [F]160mm, [R]140mm
MANETE FRANA	SRAM Force AXS E1
PINIOANE	SRAM Force, 12-speed, 10x33
LANT	SRAM Force E1
ANGRENAJ	SRAM Force E1 DUB, 35/48 with power meter XS:165mm, S:165mm, M:170mm, M/L:170mm, L:172.5mm, XL:172.5mm
BOTTOM BRACKET	SRAM, press fit

ROTI	
JANTE	Giant SLR 1 50 Carbon Disc WheelSystem, [F]50mm, [R]50mm
BUTUCI	[F] Giant Low Friction Hub, CenterLock, [R] Giant Low Friction Hub, 30T ratchet driver, CenterLock, 12mm thru-axle
SPITE	Sapim
ANVELOPE	CADEX Road Race GC, tubeless, 700x28c, folding
EXTRAS	computer mount, bottle cages, tubeless prepared, 32mm max tire size
LIMITS	
MAX TIRE CLEARANCE	32mm

## GEOMETRIE

CADRU	XS	S	M	ML	L	XL
Seat Tube Length (mm)	465	500	520	545	575	595
Seat Tube Angle	74,5°	74,0°	73,5°	73,0°	73,0°	72,5°
Top Tube Length (mm)	520	535	550	565	580	600
Head Tube Length (mm)	120	130	145	165	185	200
Head Tube Angle	71,0°	72,3°	73,0°	73,0°	73,0°	73,0°
Fork Rake (mm)	45	45	45	45	45	45
Trail (mm)	70,5	62,5	57,8	57,8	57,8	57,8
Wheelbase (mm)	976	977	980	991	1006	1020
Chain Stay Length (mm)	405	405	405	405	405	405
Bottom Bracket Drop (mm)	72	70	70	67	67	67
Stack (mm)	517	528	545	562	581	596
Reach (mm)	376	383	388	393	402	412
Stand Over Height (mm)	722	753	770	794	821	834
Handlebar Width (mm)	380	380	400	400	420	420
Stem Length (mm)	80	90	100	110	110	120
Crank Length (mm)	165	165	170	170	172,5	172,5

Toate specificatiile enumerate se pot schimba fara notificare prealabila.