

PROPEL ADVANCED PRO 0-AXS



SPECS

| FRAME | |
|-------------------------|--|
| SIZES | XS, S, M, M/L, L, XL |
| COLORS | Obsidian Pulse |
| FRAME | Advanced-grade Composite, 12x142mm thru-axle, disc |
| FORK | Advanced SL-grade Composite, full-composite OverDrive Aero steerer, 12x100mm thru-axle, disc |
| COMPONENTS | |
| HANDLEBAR | Giant Contact SLR 0 Aero Integrated XS:380/360mm, S:380/360mm, M:400/370mm, M/L:400/370mm, L:420/390mm, XL:420/390mm |
| GRIPS | Stratus Lite 2.0 |
| STEM | Giant Contact SLR 0 Aero Integrated XS:80mm, S:90mm, M:100mm, M/L:110mm, L:110mm, XL:120mm |
| SEATPOST | Giant Vector, composite, -5/+15mm offset |
| SADDLE | Giant Fleet SL |
| DRIVETRAIN | |
| SHIFTERS | SRAM Force AXS E1 |
| FRONT DERAILLEUR | SRAM Force AXS E1 |
| REAR DERAILLEUR | SRAM Force AXS E1 |
| BRAKES | SRAM Force E1 hydraulic, SRAM PaceLine X rotors [F]160mm, [R]140mm |
| BRAKE LEVERS | SRAM Force AXS E1 |
| CASSETTE | SRAM Force, 12-speed, 10x33 |
| CHAIN | SRAM Force E1 |
| CRANKSET | SRAM Force E1 DUB, 35/48 with power meter XS:165mm, S:165mm, M:170mm, M/L:170mm, L:172.5mm, XL:172.5mm |
| BOTTOM BRACKET | SRAM, press fit |

| WHEELS | |
|---------------|--|
| RIMS | Giant SLR 0 50 Carbon WheelSystem, [F]50mm, [R]50mm |
| HUBS | [F] Giant Aero Hub, CenterLock [R] Giant Aero Hub, 40T ratchet driver, CenterLock 12mm thru-axle |
| SPOKES | Aero Carbon |
| TIRES | CADEX Aero, tubeless, 700x28c (28mm), folding |
| EXTRAS | computer mount, water bottle cages, tubeless prepared, 32mm max tire size |

GEOMETRY

| FRAME | XS | S | M | M/L | L | XL |
|--------------------------|-------|-------|-------|-------|-------|-------|
| Seat Tube Length (mm) | 484 | 505 | 528.5 | 554 | 576 | 595 |
| Seat Tube Angle | 74.5° | 74.0° | 73.5° | 73.0° | 73.0° | 72.5° |
| Top Tube Length (mm) | 520 | 535 | 550 | 565 | 580 | 600 |
| Head Tube Length (mm) | 115 | 127 | 145 | 165 | 185 | 200 |
| Head Tube Angle | 71.5° | 72.5° | 73.0° | 73.0° | 73.0° | 73.0° |
| Fork Rake (mm) | 45 | 45 | 45 | 45 | 45 | 45 |
| Trail (mm) | 67.8 | 61.4 | 58.3 | 58.3 | 58.3 | 58.3 |
| Wheelbase (mm) | 971 | 973 | 980 | 990 | 1006 | 1020 |
| Chain Stay Length (mm) | 405 | 405 | 405 | 405 | 405 | 405 |
| Bottom Bracket Drop (mm) | 72 | 72 | 69.5 | 69.5 | 67 | 67 |
| Stack (mm) | 515 | 530 | 546 | 565 | 582 | 596 |
| Reach (mm) | 377 | 383 | 388 | 392 | 402 | 412 |
| Stand Over Height (mm) | 746 | 764 | 787 | 808 | 832 | 847 |
| Handlebar Width (mm) | 380 | 380 | 400 | 400 | 420 | 420 |
| Stem Length (mm) | 80 | 90 | 100 | 110 | 110 | 120 |
| Crank Length (mm) | 165 | 165 | 170 | 170 | 172.5 | 172.5 |
| Wheel Size | 700C | 700C | 700C | 700C | 700C | 700C |

All specifications listed are subject to change without notice.