

# PROPEL ADVANCED PRO 0 (AXS)

GIANT



## 產品規格

|           |  |
|-----------|--|
| <b>車架</b> |  |
| 尺寸        | XS, S, M, M/L  |
| 顏色        | 光譜銀  |
| 車架        | Advanced-grade Composite, 12x142mm thru-axle, disc   |
| 前叉        | Advanced SL-grade Composite, full-composite OverDrive Aero steerer, 12x100mm thru-axle, disc |

### COMPONENTS

|       |  |
|-------|--|
| 車把手   | Giant Contact SLR Aero                   |
| 把手帶/套 | Stratus Lite 2.0                         |
| 變桿    | Giant Contact SL Aero                    |
| 座桿    | Giant Vector, composite, -5/+15mm offset |
| 坐墊    | Giant Fleet SL                           |

### DRIVETRAIN

|                             |   |
|-----------------------------|---|
| 變速把手                        | SRAM Force AXS E1                         |
| 前變速器                        | SRAM Force AXS E1                         |
| 後變速器                        | SRAM Force AXS E1                         |
| 煞車系統                        | SRAM Force E1 hydraulic,                  |
| 煞車把手                        | SRAM Force AXS E1                         |
| 飛輪                          | SRAM Force, 12-speed, 10x33               |
| 鍊條                          | SRAM Force E1                             |
| 大齒盤                         | SRAM Force E1 DUB, 35/48 with power meter |
| <b>BOTTOM BRACKET (B B)</b> | SRAM, press fit                           |

|                    |  |
|--------------------|--|
| <b>輪組</b>          |  |
| 輪圈                 | Giant SLR 1 50 Carbon Disc WheelSystem,  |
| 花鼓                 | [F] Giant Low Friction Hub, CenterLock, [R] Giant Low Friction Hub, 30T ratchet driver, CenterLock, 12mm thru-axle |
| 輻條                 | Sapim  |
| 外胎                 | CADEX Road Race GC, tubeless, 700x28c, folding   |
| 其他                 | computer mount, bottle cages, tubeless prepared, 32mm max tire size  |
| <b>LIMITS</b>      |  |
| MAX TIRE CLEARANCE | 32mm   |

Price: NT\$188,000

## 車架幾何

| 車架           | XS    | S     | M     | ML    |
|--------------|-------|-------|-------|-------|
| 座(立)管長 (mm)  | 465   | 500   | 520   | 545   |
| 座(立)管角度      | 74.5° | 74.0° | 73.5° | 73.0° |
| 上管長度 (mm)    | 520   | 535   | 550   | 565   |
| 頭管長度 (mm)    | 120   | 130   | 145   | 165   |
| 頭管角度         | 71.0° | 72.3° | 73.0° | 73.0° |
| 前叉 (mm)      | 45    | 45    | 45    | 45    |
| Trail (mm)   | 70.5  | 62.5  | 57.8  | 57.8  |
| 前後輪距 (mm)    | 976   | 977   | 980   | 991   |
| 後下叉長度 (mm)   | 405   | 405   | 405   | 405   |
| 五通下降高度 (mm)  | 72    | 70    | 70    | 67    |
| 頭碗至五通高度 (mm) | 517   | 528   | 545   | 562   |
| 頭碗至五通長度 (mm) | 376   | 383   | 388   | 393   |
| 上管至地面高度 (mm) | 722   | 753   | 770   | 794   |
| 把手寬 (mm)     | 380   | 380   | 400   | 400   |
| 龍頭長度 (mm)    | 80    | 90    | 100   | 110   |
| 曲柄長度 (mm)    | 165   | 165   | 170   | 170   |

\*捷安特公司對本網站所刊載之產品資料保留修改權利，恕不另行通知(包括有關設備、規格、型號、重量、顏色和材料等)，請以實際產品為主。