

PROPEL ADVANCED PRO 0 (DI2)

GIANT



SPECS

FRAME	
SIZES	XS, S, M, M/L, L, XL
COLOURS	Prismatic Haze/Iris, Abyss Black
FRAME	Advanced-grade Composite, 12x142mm thru-axle, disc
FORK	Advanced SL-grade Composite, full-composite OverDrive Aero steerer, 12x100mm thru-axle, disc
COMPONENTS	
HANDLEBAR	Giant Contact SLR Aero XS:38cm, S:38cm, M:40cm, M/L:40cm, L:42cm, XL:42cm
GRIPS	Stratus Lite 2.0
STEM	Giant Contact SL Aero XS:80mm, S:90mm, M:100mm, M/L:110mm, L:110mm, XL:120mm
SEATPOST	Giant Vector, composite, -5/+15mm offset
SADDLE	Giant Fleet SL
DRIVETRAIN	
SHIFTERS	Shimano Ultegra Di2 ST-R8170
FRONT DERAILLEUR	Shimano Ultegra Di2 FD-R8150
REAR DERAILLEUR	Shimano Ultegra Di2 RD-R8150
BRAKES	Shimano Ultegra Di2 hydraulic, Shimano RT-CL800 rotors [F]160mm, [R]140mm
BRAKE LEVERS	Shimano Ultegra Di2 hydraulic
CASSETTE	Shimano Ultegra, 12-speed, 11x30
CHAIN	Shimano Ultegra, CN-M8100
CRANKSET	Shimano Ultegra, 36/52, with Giant Power Pro power meter, XS:165mm, S:165mm, M:170mm, M/L:170mm, L:172.5mm, XL:172.5mm
BOTTOM BRACKET	Shimano, press fit

WHEELS	
RIMS	Giant SLR 1 50 Carbon Disc WheelSystem, [F]50mm, [R]50mm
HUBS	[F] Giant Low Friction Hub, CenterLock, [R] Giant Low Friction Hub, 30T ratchet driver, CenterLock, 12mm thru-axle
SPOKES	Sapim
TYRES	CADEX Road Race GC, tubeless, 700x28c, folding
EXTRAS	computer mount, bottle cages, tubeless prepared, 32mm max tire size
LIMITS	
MAX TIRE CLEARANCE	32mm

Price: €6,349.00

GEOMETRY

FRAME	S	M	ML	L	XL
Seat Tube Length (mm)	500	520	545	575	595
Seat Tube Angle	74.0°	73.5°	73.0°	73.0°	72.5°
Top Tube Length (mm)	535	550	565	580	600
Head Tube Length (mm)	130	145	165	185	200
Head Tube Angle	72.3°	73.0°	73.0°	73.0°	73.0°
Fork Rake (mm)	45	45	45	45	45
Trail (mm)	62.5	57.8	57.8	57.8	57.8
Wheelbase (mm)	977	980	991	1006	1020
Chain Stay Length (mm)	405	405	405	405	405
Bottom Bracket Drop (mm)	70	70	67	67	67
Stack (mm)	528	545	562	581	596
Reach (mm)	383	388	393	402	412
Stand Over Height (mm)	753	770	794	821	834
Handlebar Width (mm)	380	400	400	420	420
Stem Length (mm)	90	100	110	110	120
Crank Length (mm)	165	170	170	172.5	172.5

All specifications listed are subject to change without notice.