

PROPEL ADVANCED PRO 0-DI2

GIANT



ESPECIFICACIONES

CUADRO	
TALLAS	XS, S, M, M/L, L, XL
COLORES	Abyss Teal/Fluorescent Mint, Obsidian Pulse
CUADRO	Advanced-grade Composite, 12x142mm thru-axle, disc
HORQUILLA	Advanced SL-grade Composite, full-composite OverDrive Aero steerer, 12x100mm thru-axle, disc
COMPONENTES	
MANILLAR	Giant Contact SLR 0 Aero Integrated XS:380/360mm, S:380/360mm, M:400/370mm, M/L:400/370mm, L:420/390mm, XL:420/390mm
PUÑOS	Stratus Lite 2.0
POTENCIA	Giant Contact SLR 0 Aero Integrated XS:80mm, S:90mm, M:100mm, M/L:110mm, L:110mm, XL:120mm
TIJA DE SILLÍN	Giant Vector, composite, -5/+15mm offset
SILLÍN	Giant Fleet SL
TRANSMISIÓN	
MANETAS DE CAMBIO	Shimano Ultegra Di2 ST-R8170
DESVIADOR	Shimano Ultegra Di2 FD-R8150
CAMBIO TRASERO	Shimano Ultegra Di2 RD-R8150
FRENOS	Shimano Ultegra Di2 hydraulic, Shimano RT-CL800 rotors [F]160mm, [R]140mm
PALANCAS DE FRENOS	Shimano Ultegra Di2 hydraulic
CASETTE	Shimano Ultegra, 12-speed, 11x34
CADENA	Shimano Ultegra, CN-M8100
JGO. PLATOS Y BIELAS	Shimano Ultegra, 36/52, with Giant Power Pro power meter XS:165mm, S:165mm, M:170mm, M/L:170mm, L:172.5mm, XL:172.5mm
CAJA DE PEDALIER	Shimano, press fit

RUEDAS	
LLANTAS	Giant SLR 0 50 Carbon WheelSystem, [F]50mm, [R]50mm
BUJES	[F] Giant Aero Hub, CenterLock [R] Giant Aero Hub, 40T ratchet driver, CenterLock 12mm thru-axle
RADIOS	Aero Carbon
CUBIERTAS	CADEX Aero, tubeless, 700x28c (28mm), folding
EXTRAS	computer mount, water bottle cages, tubeless prepared, 32mm max tire size

Precio: 6.599,00 €

GEOMETRÍA

CUADRO	XS	S	M	M/L	L	XL
Longitud del tubo del sillín (mm)	484	505	528,5	554	576	595
Ángulo del tubo del sillín	74,5°	74,0°	73,5°	73,0°	73,0°	72,5°
Longitud del tubo superior (mm) (mm)	520	535	550	565	580	600
Longitud del tubo de dirección (mm) (mm)	115	127	145	165	185	200
Ángulo del tubo de dirección	71,5°	72,5°	73,0°	73,0°	73,0°	73,0°
Inclinación de la horquilla (mm)	45	45	45	45	45	45
Trail (mm) (mm)	67,8	61,4	58,3	58,3	58,3	58,3
Distancia entre ejes (mm) (mm)	971	973	980	990	1006	1020
Longitud de la vaina (mm) (mm)	405	405	405	405	405	405
Caída del eje de pedalier (mm) (mm)	72	72	69,5	69,5	67	67
Stack (mm) (mm)	515	530	546	565	582	596
Reach (mm) (mm)	377	383	388	392	402	412
Altura del suelo al tubo (mm) (mm)	746	764	787	808	832	847
Ancho del manillar (mm) (mm)	380	380	400	400	420	420
Longitud de la potencia (mm) (mm)	80	90	100	110	110	120
Longitud de las bielas (mm) (mm)	165	165	170	170	172,5	172,5
Tamaño de ruedas	700C	700C	700C	700C	700C	700C

Giant se reserva el derecho a modificar especificaciones, precios o colores sin previo aviso.