

PROPEL ADVANCED PRO 0 DI2

GIANT



ESPECIFICACIONES

CUADRO	
TALLAS	XS, S, M, M/L, L, XL
COLORES	Black Currant/Chrome
CUADRO	Advanced-Grade Composite, disc
TIJERA	Advanced SL-Grade Composite, full-composite OverDrive Aero steerer, disc
AMORTIGUADOR	N/A
COMPONENTES	
MANUBRIO	Giant Contact SLR Aero XS:40cm, S:40cm, M:42cm, M/L:42cm, L:44cm, XL:44cm
GRIPS	Stratus Lite 2.0
POTENCIA	Giant Contact SL Aero, OverDrive Aero XS:80mm, S:90mm, M:100mm, M/L:110mm, L:110mm, XL:120mm
POSTE DE ASIENTO	Giant Vector, composite, -5/+15mm offset
ASIENTO	Giant Fleet SL
PEDALES	N/A
TRANSMISIÓN	
MANETAS DE CAMBIO	Shimano Ultegra Di2 ST-R8170
DESVIADOR	Shimano Ultegra Di2 FD-R8150
CAMBIO TRASERO	Shimano Ultegra Di2 RD-R8150
FRENOS	Shimano Ultegra Di2 hydraulic, Shimano RT-MT800 rotors [F]160mm, [R]140mm
PALANCAS DE FRENOS	Shimano Ultegra Di2 hydraulic
CASSETTE	Shimano Ultegra, 12-speed, 11x30
CADENA	Shimano Ultegra, CN-M8100
MULTIPLICACIÓN	Shimano Ultegra, 36/52, XS:170mm, S:170mm, M:172.5mm, M/L:172.5mm, L:175mm, XL:175mm
EJE DE CENTRO	Shimano, press fit

RUEDAS	
RUEDAS	Giant SLR 1 50 Carbon Disc WheelSystem, [F]50mm, [R]50mm
MAZAS	[F] Giant Low Friction Hub, CenterLock, 12mm thru-axle, [R] Giant Low Friction Hub, 30t ratchet driver, CenterLock, 12mm thru-axle,
RAYOS	SAPIM CX-Ray
NEUMÁTICOS	CADEX Race, tubeless, 700x25c (26.5mm), folding
EXTRAS	computer mount, water bottle cages, tubeless prepared, 32mm max tire size
LIMITS	
MAX TIRE CLEARANCE	32mm

Precio: \$161,990.00

GEOMETRÍA

CUADRO	XS	S	M	ML	L	XL
Longitud de la Base del Poste de Asiento (mm)	465	500	520	545	575	595
Seat Post Insertion Depth (mm)	70	70	70	70	70	70
Ángulo de la Base del Poste de Asiento	74.5°	74.0°	73.5°	73.0°	73.0°	72.5°
Longitud del Tubo Superior (mm)	520	535	550	565	580	600
Longitud del Telescopio (mm)	120	130	145	165	185	200
Ángulo del Telescopio	71.0°	72.3°	73.0°	73.0°	73.0°	73.0°
Rake (mm)	45	45	45	45	45	45
Trail (mm)	70.5	62.5	57.8	57.8	57.8	57.8
Distancia entre Ejes (mm)	976	977	980	991	1006	1020
Longitud de Vaina Inferior (mm)	405	405	405	405	405	405
Caída del Eje de Centro (mm)	72	70	70	67	67	67
Stack (mm)	517	528	545	562	581	596
Reach (mm)	376	383	388	393	402	412
Altura del Tubo Superior al Suelo (mm)	722	753	770	794	821	834
Ancho del Manubrio (mm)	400	400	420	420	440	440
Longitud de la Potencia (mm)	80	90	100	110	110	120
Longitud de la Biela (mm)	170	170	172.5	172.5	175	175
Tamaño de las Ruedas	700C	700C	700C	700C	700C	700C

Todas las especificaciones están sujetas a cambios sin previo aviso.